


# ShawContract®

## Function 5.0


Collection	<b>Function + Flow</b>	
Style Number	<b>4388V</b>	
Construction	<b>Commercial Luxury Vinyl Tile</b>	
Class / ASTM F1700	<b>Class III, Type B</b>	
Finish	<b>ExoGuard+®</b>	
	U.S.	Metric
Nominal Dimensions	<b>18 in w x 18 in l</b>	<b>46 cm w x 46 cm l</b>
Actual Dimensions	<b>18.00 in w x 18.00 in l</b>	<b>45.72 cm w x 45.72 cm l</b>
Wear Layer Thickness	<b>22 mil (0.022 in)</b>	<b>0.56 mm</b>
Overall Thickness	<b>0.197 in</b>	<b>5 mm</b>
Edge Profile	<b>Tiny Bevel</b>	
Installation Type	<b>Dry Back</b>	
Installation	<b>Direct Glue</b>	
Recommended Adhesive	<b>S150-95 Resilient Tile Spray, 4200 Resilient Tile 4 Gallon, 2200 Resilient Tile 4 Gallon, 2200 Resilient Tile 1 Gallon or 4151 Multi-Use Premium 4 Gallon</b>	



### Packaging

Pieces per Carton	<b>10 pcs</b>	
Area per Carton	<b>22.5 sq ft</b>	<b>2.09 sq m</b>
Weight per Carton	<b>44.74 lbs</b>	<b>20.29 kg</b>

### Recommended Installation Method



### Coordinating Products

LVT: Flow 2.5, Function 2.5, Flow 5.0, Flow 5.0 Lt

### Performance + Testing

Static Load (ASTM F970)	<b>Passes (Modified), *1500 lbs</b>	*This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary.
Residual Indentation (ASTM F1914)	<b>Passes</b>	
Resistance to Heat (ASTM F1514)	<b>Passes</b>	
Resistance to Light (ASTM F1515)	<b>Passes</b>	
Resistance to Chemicals (ASTM F925)	<b>Passes</b>	
Radiant Panel (ASTM E648)	<b>Passes, Class I</b>	
Coefficient of Friction (ASTM D2047, Slip Resistance)	<b>≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces</b>	

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

## Warranties

---

[15 Year Commercial Limited Warranty](#)

[Commercial 15 Year Underbed Bond Warranty](#)

## Diversity, Equity & Inclusion

---

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw's diverse customer base and local community. More than 42% of our spend\*\*\*\* is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

## Material Health & Environmental Certifications

---

### Climate Impact

Environmental Product Declaration (EPD)

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017

Total Recycled Content

0% (Pre-Consumer 0% | Post-Consumer 0%)

### Global Product Assessment

FloorScore® | Certified

Country of Origin | China

## WELL V2 Contribution Credit

---

X01 Fundamental Material Precautions  
Part 1: (C): Restrict Asbestos Precondition

**Absence of Asbestos**

X08 Hazardous Material Reduction  
Part 1: Limit Hazardous Materials Optimization

**Absence of Heavy Metals**

X10 Volatile Compound Reduction  
Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization

**Absence of Halogenated Flame Retardants**

X10 Volatile Compound Reduction  
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization

**Ortho-Phthalates**

X11 Long Term Emissions Control  
Part 2: Flooring Optimization

**FloorScore Certificate**

## Leed v4 Contribution Credits

---

MR Credit: Building Product Disclosure and Optimization  
Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)

**3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017**

EQ Credit: Low Emitting Materials  
Option 1: Product Category Calculations

**FloorScore Certified**

[Installation Guidelines](#)

[Maintenance Guidelines](#)

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

\*\*\*\*Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

## Available Colorways



Silica 86100  
LRV 58.7



Uniform 86120  
LRV 36



Transition 86501  
LRV 40.8



Pebble 86504  
LRV 39.3



Composite 86506  
LRV 24.5



Blend 86515  
LRV 44



Change 86520  
LRV 24.8

