

Innate Sheet

Colección	Innate + In Tandem	
Número De Estilo	4219V	
Número De Estilo De Barra De Soldadura	270VS	
clase	Tested To ASTM 1303	
Terminación	ExoGuard+®	
	U.s.	Metric
Espesor Total Del Producto	0.098 in	2.5 mm
Installation Type	Dry Back	
Instalación	Direct Glue	
Adhesivo Recomendado	4200 Reslient Sheet 4 Gallon or 4151 Multi-Use Premium 4 Gallon	

Embalaje

Tamaño Real Del Rollo	6.59 ft w x 65.61 ft l	2.01 m w x 20.00 m l
Área Por Rollo	48.07 sy/roll	40.19 sq m/roll
Peso Por Rollo	321.88 lbs	146 kg



Método De Instalación Recomendado



Non Reverse

Productos Que Combinan

None: Innate, In Tandem Sheet, In Tandem, Innate Linen Sheet, Innate Stria Tile

Desempeño + Pruebas

Flexibilidad (Astm F137)	Passes
Resistencia Al Calor (Astm F1514)	Passes
Resistencia A La Luz (Astm F1515)	Passes
Resistencia A Productos Químicos (Astm F925)	Passes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantías

[15 Años Limitado A Uso Comercial](#)
[Commercial 15 Year Underbed Bond Warranty](#)

Atributos + Certificaciones

Health & Wellbeing

Material Ingredient Transparency

Cradle to Cradle Certified™ | Nivel Plata (Versión 3.1)
Health Product Declaration (HPD) | 1000 ppm Disclosure
Declare | Compatible LBC

Climate Impact

Environmental Product Declaration (EPD)

Certificado Tercerizado De Acuerdo Con La Norma EN 15804, ISO 14025

Embodied Carbon (Cradle to Gate)

4.31 Kg CO₂/M²

Life-Cycle Carbon Emissions

Carbon Neutral

Total Recycled Content

0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

FloorScore® | Certificado

CE Marking (EN 14041) | Certificado Tercerizado

Greenguard (Certification, Gold, Private Label) | Certificado

Country of Origin | Imported

Contribución Para Créditos Leed

Crédito MR: Divulgación y optimización de productos de construcción
Ingredientes de materiales - Opción 1: Informe de ingredientes de los materiales**Health Product Declaration (HPD) | 100 Ppm Disclosure**Crédito MR: Divulgación y optimización de productos de construcción
Declaraciones ambientales de productos - Opción 1: Declaración ambiental de productos (EPD)**3rd Party Certified in Accordance with EN 15804, ISO 14025**Crédito EQ: Materiales de baja emisión
Opción 1: Cálculos de categoría de producto**FloorScore & Greenguard Gold Certified**

Installation Guidelines


Please visit www.shawcontract.com for the most current warranty information.

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways

Dove 19104
Weldrod 00500Natural 19110
Weldrod 00700Flax 19114
Weldrod 00114Concrete 19515
Weldrod 00515Umber 19715
Weldrod 00715Mineral 19760
Weldrod 00550

Corporate Headquarters +1 800 257 7429 | +1 706 532 7984 | Atlanta +1 404 853 7429 | Bengaluru +91 80 6773 0202 | Beijing +86 10 6568 588 | Chicago +1 312 467 1331 | Dubai +971 4 584 6956 | Hong Kong +852 2623 0371 | Latin America (Miami) +1 305 827 5912 | London +44 207 961 4120 | Los Angeles +1 800 233 1614 | Melbourne +61 3 9939 8543 | Mexico City +52 5010 7600 | Mumbai +91 22 6284 5050 | Nantong +86 400 800 7429 | New York +1 212 953 7429 | Paris +33 (0) 1 81 22 44 39 | San Francisco +1 415 955 1920 | Santiago +562 2431 5000 x 550 | São Paulo +55 11 3071 1702 | Shanghai +86 21 3338 4000 | Singapore +65 6733 1811 | Sydney +1 800 556 302

© 2024 Shaw Industries Group, Inc., a Berkshire Hathaway Company
May 11, 2024