

Innate Sheet

Collection	Innate + In Tandem	
Numéro De Style	4219V	
Référence De La Baguette De Soudure	270VS	
Construction	Rouleauhet Commerciale EN Polyuréthane Biosourcé Avec Fibre De Verre	
classe	Tested To ASTM 1303	
Finition	ExoGuard+®	
Épaisseur Générale Du Produit	Impérial	Métrique
	0.098 in	2.5 mm
Installation Type	Dry Back	
Installation	Direct Glue	
Adhésif Recommandé	4200 Reslient Sheet 4 Gallon or 4151 Multi-Use Premium 4 Gallon	

Emballage

Dimensions Réelles Du Rouleau	6.59 ft w x 65.61 ft l	2.01 m w x 20.00 m l
Surface Par Rouleau	48.07 sy/roll	40.19 sq m/roll
Poids Par Rouleau	321.88 lbs	146 kg



Méthodes d'Installation Conseillées



Non Reverse

Coordination Des Produits

None: Innate, In Tandem Sheet, In Tandem, Innate Linen Sheet, Innate Stria Tile

Performance + Tests Et Essai

Souplesse (Astm F137)	Passes
Résistance À La Chaleur (Astm F1514)	Passes
Résistance À La Lumière (Astm F1515)	Passes
Résistance Chimique (Astm F925)	Passes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garanties

[Limitée Commerciale De 15 Ans](#)
[Commercial 15 Year Underbed Bond Warranty](#)

Attributs + Certifications

Health & Wellbeing

Material Ingredient Transparency

Cradle to Cradle Certified™ | Niveau Argent (Version 3.1)
Health Product Declaration (HPD) | 1000 ppm Disclosure
Declare | Conforme LBC

Climate Impact

Environmental Product Declaration (EPD)

Embodied Carbon (Cradle to Gate)

Life-Cycle Carbon Emissions

Total Recycled Content

Certifié Par Une Tierce Partie Conformément Aux Normes EN 15804, ISO 14025

4.31 Kg CO₂/M²

Carbon Neutral

0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

FloorScore® | Agréé

CE Marking (EN 14041) | Certifié Par Un Tiers

Greenguard (Certification, Gold, Private Label) | Agréé

Country of Origin | Imported

Contribution Au Certificat Vert Leed

« Crédit MR : Divulgarion et optimisation des produits de construction

« Crédit MR : Divulgarion et optimisation des produits de construction

Crédit EQ : matériaux faibles émissions

Installation Guidelines

Health Product Declaration (HPD) | 100 Ppm Disclosure

3rd Party Certified in Accordance with EN 15804, ISO 14025







FloorScore & Greenguard Gold Certified

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply
and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of
this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways

					
Dove 19104 Weldrod 00500	Natural 19110 Weldrod 00700	Flax 19114 Weldrod 00114	Concrete 19515 Weldrod 00515	Umber 19715 Weldrod 00715	Mineral 19760 Weldrod 00550

