

Pathway

|                           |                                       |                         |
|---------------------------|---------------------------------------|-------------------------|
| Collection                | Pathway & Promenade                   |                         |
| Style Number              | 4281V                                 |                         |
| Construction              | Heavy Commercial Luxury Vinyl Tile    |                         |
| class                     | Class III, Type B                     |                         |
| Finish                    | ExoGuard®                             |                         |
|                           | U.s.                                  | Metric                  |
| Nominal Dimensions        | 36 in w x 36 in l                     | 91 cm w x 91 cm l       |
| Actual Dimensions         | 36.00 in w x 36.00 in l               | 91.44 cm w x 91.44 cm l |
| Wear Layer Thickness      | 20 mil (0.02 in)                      | 0.51 mm                 |
| Overall Product Thickness | 0.197 in                              | 5 mm                    |
| Edge Profile              | Micro-Bevel                           |                         |
| Installation Type         | Loose Lay                             |                         |
| Installation              | Direct Glue, Floating Or Perimeter Gl |                         |

Packaging

|                |             |           |
|----------------|-------------|-----------|
| Pieces Per Box | 4 pcs       |           |
| Area Per Box   | 35.99 sq ft | 3.34 sq m |
| Weight Per Box | 71.34 lbs   | 32.36 kg  |



Recommended Installation Method



Performance + Testing

|                                                       |                                                                                     |
|-------------------------------------------------------|-------------------------------------------------------------------------------------|
| Resistance To Heat (Astm F1514)                       | Passes                                                                              |
| Resistance To Light (Astm F1515)                      | Passes                                                                              |
| Resistance To Chemicals (Astm F925)                   | Passes                                                                              |
| Coefficient Of Friction (Astm D2407, Slip Resistance) | ≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces |

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

15 Year Commercial Limited

Diversity, Equity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw's diverse customer base and local community. More than 42% of our spend\*\*\*\*\* is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and openingnew markets for growth.

Attributes + Certifications

|                                         |                                                                              |
|-----------------------------------------|------------------------------------------------------------------------------|
| Health & Wellbeing                      |                                                                              |
| Material Ingredient Transparency        | Health Product Declaration (HPD)   1000 ppm Disclosure                       |
| Climate Impact                          |                                                                              |
| Environmental Product Declaration (EPD) | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017 |
| Embodied Carbon (Cradle to Gate)        | 6.05 Kg CO <sub>2</sub> /M <sup>2</sup>                                      |
| Total Recycled Content                  | 0% (Pre-Consumer 0%   Post-Consumer 0%)                                      |
| Global Product Assessment               | FloorScore®   Certified                                                      |
|                                         | Country of Origin   China                                                    |

Green Leed Contribution Credit

|                                                                                                                                                   |                                                                              |
|---------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------|
| MR Credit: Building Product Disclosure and Optimization<br>Material Ingredients - Option 1: Material Ingredient Reporting                         | Health Product Declaration (HPD)   100 Ppm Disclosure                        |
| MR Credit: Building Product Disclosure and Optimization<br>Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD) | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017 |
| EQ Credit: Low Emitting Materials<br>Option 1: Product Category Calculations                                                                      | FloorScore Certified                                                         |

Installation Guidelines


Maintenance Guidelines

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.


This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.  
\*\*\*\*\*Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.


Available Colorways




Radiance 01041  
V3 - Moderate Variation



Attraction 05081  
V3 - Moderate Variation



Oneness 05082  
V3 - Moderate Variation



Union 05085  
V3 - Moderate Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

