

Observe

Style Number	4566V	
Product Type	Heavy Commercial Pvc-Free Ecoworx Resilient	
Collection	Art + Science	
Construction	Standard	Data + Performance
Type of Floorcovering	EN 1307	EcoWorx resilient
Classification	ISO 10874	class 34 very heavy commercial use
Total Mass	EN ISO 23997	3.49 kg/m²
Total Thickness	EN ISO 24346	2.5 mm
Finish		ExoGuard+®
Dimensions	EN 994	21.01 cm x 129.01 cm 16 tiles (4.33 sq m) per box
Weight per Box		16.52 kg




Performance


Flammability	EN 13501-1	Bfl-S1
Thermal Resistance m ² K/W	ISO 8302	0.013 m² K/W
Slip Resistance	BS 7976-2	Smooth Emboss: PTV Dry 61 PTV Wet 44 (pendulum)
	DIN 51130	R10
Dimensional Stability	EN ISO 23999	≤0.15%
Castor Chair	EN 425, ISO 4918	no damage
Impact Sound Reduction	BS EN ISO 10140	ΔLw 9dB/20dB with 2mm underlay
Colour Fastness to Light	BS EN ISO 105-BO2	8

15 Year Commercial Limited System Warranty subject to installation in full accordance with the manufacturer's instructions and a regular effective cleaning and maintenance programme. Second location warranties are available with the use of non-adhesive IOBAC Magtabs and Tabit accessories.

Recommended Installation Method



colour and visual variation index




Coordinating Products

PVC-Free: Pivot

Product Transparency

Shaw Contract is dedicated to providing clients with a building chemistry that's safe and dependable. Working together, we will help you meet your goals as they pertain to material health. Engineered Hardwood products are Cradle to Cradle Certified™ Silver and assessed for impacts on human health and the environment.



ΔLw 9dB/20dB with 2mm underlay

Corporate Headquarters +1 800 257 7429 | +1 706 532 7984 | Atlanta +1 404 853 7429 | Bengaluru +91 80 6773 0202 | Beijing +86 10 6568 588 | Chicago +1 312 467 1331 | Dubai +971 4 584 6956 | Hong Kong +852 2623 0371 | London +44 207 961 4120 | Los Angeles +1 800 233 1614 | Melbourne +61 3 9939 8543 | Mexico City +55 5010 7600 | Mumbai +91 22 6284 5050 | Nantong +86 400 800 7429 | New York +1 212 953 7429 | Paris +33 (0) 1 81 22 44 39 | San Francisco +1 415 955 1920 | Shanghai +86 21 3338 4000 | Singapore +65 6733 1811 | Sydney +61 800 556 302

Material Health & Environmental Certifications

Greenhealth Approved	Yes
Health Product Declaration (HPD)	1000 ppm Disclosure
Environmental Product Declaration (EPD)	in Accordance with ISO 14025:2006 And EN 15804:2012+a2:2019/Ac:2021
Declare	LBC Compliant
Embodied Carbon (Cradle to Gate)	5.2 Kg Co ₂ /M ²
Life-Cycle Carbon Emissions	Carbon Neutral
Environmental Guarantee	Environmental Guarantee* Through Our Environmental Guarantee, Shaw Pledges to Transport And Recycle Any Ecoworx Resilient Within The United States And Canada At No Cost to The Customer.
Total Recycled Content	25% (Pre-Consumer 0% Post-Consumer 25%)
Country of Origin**	Germany

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization	Absence of Heavy Metals
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization	Absence of Halogenated Flame Retardants
X10 Volatile Compound Reduction Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization	Ortho-Phthalates
X11 Long Term Emissions Control Part 2: Flooring Optimization	Green Guard Gold Certified
X14 Material Transparency Part 1: Promote Ingredient Disclosure Optimization	Health Product Declaration (HPD) 1000 Ppm Disclosure


Leed v4 Contribution Credits

MR Credit: Building Product Disclosure and Optimization Material Ingredients - Option 1: Material Ingredient Reporting	Health Product Declaration (HPD) 1000 Ppm Disclosure
---	--

Additional Information




* To learn more about the recyclability of our products and our Environmental Guarantee, please visit shawcontract.com/sustainability .	
**Meets or exceeds all local and national regulations in country of manufacture.	
Installation	Please visit www.shawcontract.com for the most current warranty information.
Maintenance	Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.
	This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
	Visit shawcontract.com/testing for more information.

Light Reflectance Value

				
Regenerate 00103 LRV 33.7 L* 64.74 V2 - Slight Variation	Edition 00516 LRV 24.5 L* 56.61 V2 - Slight Variation	Divert 00520 LRV 39.9 L* 69.42 V2 - Slight Variation	Outlook 00535 LRV 18.8 L* 50.48 V2 - Slight Variation	Sustain 00595 LRV 24.8 L* 56.89 V3 - Moderate Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1  Uniform Appearance	V2  Slight Variation	V3  Moderate Variation	V4  Substantial Variation
---	--	---	--

