

Nordic 2.5


Collection	Nordic	
Style Number	4446V	
Construction	Heavy Commercial Luxury Vinyl Tile	
Finish	ExoGuard+®	
	U.s.	Metric
Nominal Dimensions	7 in w x 48 in l	18 cm w x 122 cm l
Actual Dimensions	7.25 in w x 48.00 in l	18.42 cm w x 121.92 cm l
Wear Layer Thickness	22 mil (0.022 in)	0.56 mm
Overall Thickness	0.098 in	2.5 mm
Edge Profile	Micro-Bevel	
Installation Type	Dry Back	
Installation	Direct Glue	
Recommended Adhesive	S150-95 Resilient Tile Spray, 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail or 4151 Multi-Use Premium 4 Gallon	

Packaging

Pieces Per Carton	16 pcs	
Area Per Carton	38.66 sq ft	3.59 sq m
Weight Per Carton	34.42 lbs	15.61 kg



Recommended Installation Method



Coordinating Products

LVT: Nordic 5.0

Performance + Testing

Static Load (ASTM F970)	Passes (Modified), *1500 lbs	*This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary.
Residual Indentation (ASTM F1914)	Passes	
Resistance to Heat (ASTM F1514)	Passes	
Resistance to Light (ASTM F1515)	Passes	
Resistance to Chemicals (ASTM F925)	Passes	
Radiant Panel (ASTM E648)	Passes, Class I	
coefficient of friction (ASTM D2407, slip resistance)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces	
Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.		

Warranties

[15 Year Commercial Limited](#)

Material Health & Environmental Certifications

Health & Wellbeing

Indoor Air Quality

FloorScore® | Certified

Climate Impact

Total Recycled Content

0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

Country of Origin | China

Green Leed Contribution Credit

EQ Credit: Low Emitting Materials  
Option 1: Product Category Calculations

FloorScore® Certified

[Installation Guidelines](#)  
[Maintenance Guidelines](#)


Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information.  
Specifications are subject to nominal manufacturing variance. Material supply  
and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of  
this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways

					
Aspen 77100 LRV 54.5   L* 78.76 V2 - Slight Variation	Natural 77101 LRV 42.2   L* 71.03 V2 - Slight Variation	Honey 77103 LRV 26.8   L* 58.83 V2 - Slight Variation	Alder 77104 LRV 25.5   L* 57.57 V3 - Moderate Variation	Calm 77111 LRV 36.8   L* 67.16 V2 - Slight Variation	Blonde 77112 LRV 37.6   L* 67.73 V2 - Slight Variation
					
Driftwood 77120 LRV 30.6   L* 62.16 V3 - Moderate Variation	Birch 77140 LRV 35.8   L* 66.35 V2 - Slight Variation	Fir 77155 LRV 42   L* 70.85 V2 - Slight Variation	Radiant 77710 LRV 21.1   L* 53.08 V2 - Slight Variation	Redwood 77720 LRV 22   L* 54.07 V2 - Slight Variation	Elm 77721 LRV 22.7   L* 54.81 V2 - Slight Variation



 **Quick Ship** Immediately - In Stock Australia

**Color and Visual Variation Index**

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

