

Nordic 2.5

Colección	Nordic	
Número De Estilo	4446V	
Construcción	Heavy Commercial Luxury Vinyl Tile	
clase		
Terminación	ExoGuard+®	
	U.s.	Metric
Dimensiones Nominales	7 in w x 48 in l	18 cm w x 122 cm l
Dimensiones Reales	7.25 in w x 48.00 in l	18.42 cm w x 121.92 cm l
Desgaste De La Capa De Uso	22 mil (0.022 in)	0.56 mm
Espesor Total Del Producto	0.098 in	2.5 mm
Perfil De Borde	Micro-Biselado	
Installation Type	Dry Back	
Instalación	Direct Glue	
Adhesivo Recomendado	S150-95 Resilient Tile Spray, 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail or 4151 Multi-Use Premium 4 Gallon	

Embalaje

Piezas Por Caja	16 pcs	
Área Por Caja	38.66 sq ft	3.59 sq m
Peso Por Caja	34.42 lbs	15.61 kg



Método De Instalación Recomendado



Productos Que Combinan

LVT: Nordic 5.0

Desempeño + Pruebas

Carga Estática (Astm F970)	Passes (Modified), *1500 lbs	Esta Prueba Tiene La Función De Comparar Propiedades Relativas De Diferentes Estilos Y Construcciones. Los Resultados Se Basan En Una Prueba De Laboratorio Y Se Utilizan Con Fines Comparativos: El Límite De Carga En La Vida Real Puede Variar.
Margen Adicional Residual (Astm F1914)	Passes	
Resistencia Al Calor (Astm F1514)	Passes	
Resistencia A La Luz (Astm F1515)	Passes	
Resistencia A Productos Químicos (Astm F925)	Passes	
Panel Radiante (Astm E648)	Passes, Class I	
Coeficiente De Fricción (Astm D2407, Resistencia Al Deslizamiento)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces	
Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.		

Garantías

- 15 Años Limitado A Uso Comercial
- Commercial 15 Year Underbed Bond Warranty

Atributos + Certificaciones

Health & Wellbeing	
Indoor Air Quality	FloorScore® Certificado
Climate Impact	
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	Country of Origin China

Contribución Para Créditos Leed

Crédito EQ: Materiales de baja emisión	FloorScore Certified
Opción 1: Cálculos de categoría de producto	
Installation Guidelines	Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice. This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited. *****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs. Visit shawcontract.com/testing for more information.
Maintenance Guidelines	

Available Colorways

 <div>Aspen 77100 LRV 54.5 L* 78.76 V2 - Slight Variation</div>	 <div>Natural 77101 LRV 42.2 L* 71.03 V2 - Slight Variation</div>	 <div>Honey 77103 LRV 26.8 L* 58.83 V2 - Slight Variation</div>	 <div>Alder 77104 LRV 25.5 L* 57.57 V3 - Moderate Variation</div>	 <div>Calm 77111 LRV 36.8 L* 67.16 V2 - Slight Variation</div>	 <div>Blonde 77112 LRV 37.6 L* 67.73 V2 - Slight Variation</div>
 <div>Driftwood 77120 LRV 30.6 L* 62.16 V3 - Moderate Variation</div>	 <div>Birch 77140 LRV 35.8 L* 66.35 V2 - Slight Variation</div>	 <div>Fir 77155 LRV 42 L* 70.85 V2 - Slight Variation</div>	 <div>Radiant 77710 LRV 21.1 L* 53.08 V2 - Slight Variation</div>	 <div>Redwood 77720 LRV 22 L* 54.07 V2 - Slight Variation</div>	 <div>Elm 77721 LRV 22.7 L* 54.81 V2 - Slight Variation</div>
 <div>Balance 77755 LRV 30.7 L* 62.29 V2 - Slight Variation</div>	 <div>Golden 77756 LRV 15.2 L* 45.94 V3 - Moderate Variation</div>				

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

