

Nordic 2.5

Collection	Nordic	
Numéro De Style	4446V	
Construction	Carreau De Vinyle De Luxe Commercial Lourd	
classe		
Finition	ExoGuard+®	
	Impérial	Métrique
Dimensions Nominales	7 in w x 48 in l	18 cm w x 122 cm l
Dimensions Réelles	7.25 in w x 48.00 in l	18.42 cm w x 121.92 cm l
Épaisseur De La Couche d'Usure	22 mil (0.022 in)	0.56 mm
Épaisseur Générale Du Produit	0.098 in	2.5 mm
Profil Du Bord	Micro-Biseau	
Installation Type	Dry Back	
Installation	Direct Glue	
Adhésif Recommandé	S150-95 Resilient Tile Spray, 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail or 4151 Multi-Use Premium 4 Gallon	

Emballage

Pièces Par Carton	16 pcs	
Surface Par Carton	38.66 sq ft	3.59 sq m
Poids Par Carton	34.42 lbs	15.61 kg



Méthodes d'Installation Conseillées



Coordination Des Produits

LVT: Nordic 5.0

performance + Tests et essai

charge statique (ASTM F970)	Passes (Modified), *1500 lbs	*This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary.
poinçonnement rémanent (ASTM F1914)	Passes	
résistance à la chaleur (ASTM F1514)	Passes	
résistance à la lumière (ASTM F1515)	Passes	
résistance chimique (ASTM F925)	Passes	
Essai au panneau radiant (Astm E648)	Passes, Class I	Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.
coefficient de frottement (ASTM D2407, résistance au glissement)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces	

Garanties

[Limitée Commerciale De 15 Ans](#)  
[Commercial 15 Year Underbed Bond Warranty](#)

Attributs + Certifications

Health & Wellbeing	
Indoor Air Quality	FloorScore®   Agréé
Climate Impact	
Environmental Product Declaration (EPD)	Certifié Par Une Tierce Partie Conformément Aux Normes ISO 14025, EN 15804 Et ISO 21930:2017
Total Recycled Content	0% (Pre-Consumer 0%   Post-Consumer 0%)
Global Product Assessment	Country of Origin   Imported

Contribution Au Certificat Vert Leed

Crédit EQ : matériaux faibles émissions	<b>FloorScore Certified</b>
<a href="#">Installation Guidelines</a>	Please visit <a href="http://www.shawcontract.com">www.shawcontract.com</a> for the most current warranty information.
<a href="#">Maintenance Guidelines</a>	Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.
	This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
	Visit <a href="http://shawcontract.com/testing">shawcontract.com/testing</a> for more information.

Available Colorways

					
Aspen 77100 LRV 54.5   L* 78.76 V2 - Slight Variation	Natural 77101 LRV 42.2   L* 71.03 V2 - Slight Variation	Honey 77103 LRV 26.8   L* 58.83 V2 - Slight Variation	Alder 77104 LRV 25.5   L* 57.57 V3 - Moderate Variation	Calm 77111 LRV 36.8   L* 67.16 V2 - Slight Variation	Blonde 77112 LRV 37.6   L* 67.73 V2 - Slight Variation
					
Driftwood 77120 LRV 30.6   L* 62.16 V3 - Moderate Variation	Birch 77140 LRV 35.8   L* 66.35 V2 - Slight Variation	Fir 77155 LRV 42   L* 70.85 V2 - Slight Variation	Radiant 77710 LRV 21.1   L* 53.08 V2 - Slight Variation	Redwood 77720 LRV 22   L* 54.07 V2 - Slight Variation	Elm 77721 LRV 22.7   L* 54.81 V2 - Slight Variation



Balance 77755

LRV 30.7 | L\* 62.29

V2 - Slight Variation

Golden 77756

LRV 15.2 | L\* 45.94

V3 - Moderate Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

