

Nordic 2.5

Coleção	Nordic	
Número Do Produto	4446V	
Construção	Heavy Commercial Luxury Vinyl Tile	
classe		
Acabamento	ExoGuard+®	
	U.s.	Metric
Dimensões Nominais	7 in w x 48 in l	18 cm w x 122 cm l
Dimensões Reais	7.25 in w x 48.00 in l	18.42 cm w x 121.92 cm l
Espessura Da Camada De Uso	22 mil (0.022 in)	0.56 mm
Espessura Total Do Produto	0.098 in	2.5 mm
Perfil De Borda	Micro-Chanfrado	
Installation Type	Dry Back	
Instalação	Direct Glue	
Adesivo Recomendado	S150-95 Resilient Tile Spray, 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail or 4151 Multi-Use Premium 4 Gallon	

Empacotamento

Peças Por Caixa	16 pcs	
Área Por Caixa	38.66 sq ft	3.59 sq m
Peso Por Caixa	34.42 lbs	15.61 kg



Método De Instalação Recomendado



Produtos Coordenados

LVT: Nordic 5.0

Desempenho + Teste

Carga Estática (Astm F970)	Passes (Modified), *1500 lbs
Recuo Residual (Astm F1914)	Passes
Resistência Ao Calor (Astm F1514)	Passes
Resistência À Luz (Astm F1515)	Passes
Resistência A Produtos Químicos (Astm F925)	Passes
Painel Radiante (Astm E648)	Passes, Class I

Este Teste Tem Como Objetivo Comparar Propriedades Relativas De Diferentes Estilos E Construções. Os Resultados São Baseados Em Um Teste De Laboratório E Usados Para Fins Comparativos - O Limite De Carga Na Vida Real Pode Variar.

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantias

[15 Anos Comercial Limitada](#)  
[Commercial 15 Year Underbed Bond Warranty](#)

Atributos + Certificações

Climate Impact	
Total Recycled Content	0% (Pre-Consumer 0%   Post-Consumer 0%)
Global Product Assessment	<a href="#">FloorScore®   Certificado</a> Country of Origin   China

Crédito De Contribuição

Crédito de EQ: Materiais de baixa emissão  
Opção 1: cálculos de categoria de produto

Installation Guidelines  
Maintenance Guidelines

FloorScore Certified

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

\*\*\*\*\*Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways

					
Aspen 77100 LRV 54.5 V2 - Slight Variation	Natural 77101 LRV 42.2 V2 - Slight Variation	Honey 77103 LRV 26.8 V2 - Slight Variation	Alder 77104 LRV 25.5 V3 - Moderate Variation	Calm 77111 LRV 36.8 V2 - Slight Variation	Blonde 77112 LRV 37.6 V2 - Slight Variation
					
Driftwood 77120 LRV 30.6 V3 - Moderate Variation	Birch 77140 LRV 35.8 V2 - Slight Variation	Fir 77155 LRV 42 V2 - Slight Variation	Radiant 77710 LRV 21.1 V2 - Slight Variation	Redwood 77720 LRV 22 V2 - Slight Variation	Elm 77721 LRV 22.7 V2 - Slight Variation



Balance 77755  
LRV 30.7  
V2 - Slight Variation

Golden 77756  
LRV 15.2  
V3 - Moderate Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

