

Traction Sole


| | | |
|---------------------------|---|--------|
| Collection | Tractionsafety | |
| Style Number | 4492V | |
| Welding Rod Style Number | 184CA | |
| class | | |
| Finish | ExoGuard® | |
| | U.s. | Metric |
| Overall Product Thickness | 0.079 in | 2 mm |
| Installation Type | Dry Back | |
| Installation | Direct Glue | |
| Recommended Adhesive | S150-95 Resilient Tile Spray Adhesive, 4200 1G Resilient Sheet Adhesive, 4200 Resilient Sheet 4 Gallon, 2200 4G Resilient Sheet Adhesive or 4151 Multi-Use Premium 4 Gallon | |

Packaging

| | | |
|------------------|------------------------|----------------------|
| Actual Roll Size | 6.56 ft w x 65.62 ft l | 2.00 m w x 20.00 m l |
| Area Per Roll | 47.84 sy/roll | 40 sq m/roll |
| Weight Per Roll | 229.28 lbs | 104 kg |



Recommended Installation Method



Coordinating Products

Sheet: Traction Aqua

performance + testing

| | |
|---|---|
| resistance to heat (ASTM F1514) | Passes |
| resistance to light (ASTM F1515) | Passes |
| resistance to chemicals (ASTM F925) | Passes |
| smoke density (ASTM E662, flaming mode) | Passes |
| radiant panel (ASTM E648) | Passes, Class I |
| coefficient of friction (ASTM D2407, slip resistance) | ≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces |
| Enhanced Slip Resistance / Surface Roughness | 20 |
| Enhanced Slip Resistance / AS 4586 Appendix D | R11 |
| Enhanced Slip Resistance / DIN 51130/EN 16165 Annex B | R11 |
| Enhanced Slip Resistance / AS 4586 Appendix A | P4 |
| Enhanced Slip Resistance / RRL Pendulum Test | 45+ |
| Enhanced Slip Resistance / EN 13845 | ESf |

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

[10 Year Commercial Limited](#)
[Commercial Limited Underbed Bond Warranty S150/4151/Lokworx+ Resilient](#)

Attributes + Certifications

Health & Wellbeing

Material Ingredient Transparency
Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure
FloorScore® | Certified

Climate Impact

Environmental Product Declaration (EPD)
Total Recycled Content

3rd Party Certified in Accordance to ISO 14044 And 14071
0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

Country of Origin | Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt

Absence of Asbestos
Absence of Heavy Metals
Absence of Halogenated Flame Retardants

Ortho-Phthalates
FloorScore Certificate

Green Leed Contribution Credit

EQ Credit: Low Emitting Materials
Option 1: Product Category Calculations

FloorScore® Certified

[Installation Guidelines](#)
[Maintenance Guidelines](#)

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.
This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
Visit shawcontract.com/testing for more information.

Available Colorways



Share 00104
Weldrod 25202



Dash 00114
Weldrod 25221



Nurture 00130
Weldrod 25212




Mettle 00240
Weldrod 25213




Sustain 00515
Weldrod 29858



Prosper 00518
Weldrod 25764



Encourage 00535
Weldrod 25233



Abundance 00740
Weldrod 25204

