

Traction Sole


Collection	Tractionsafety	
Numéro De Style	4492V	
Référence De La Baguette De Soudure	184CA	
classe		
Finition	ExoGuard®	
	Impérial	Métrique
Épaisseur Générale Du Produit	0.079 in	2 mm
Installation Type	Dry Back	
Installation	Direct Glue	
Adhésif Recommandé	4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient Sheet or 4151 Multi-Use Premium	

Emballage

Dimensions Réelles Du Rouleau	6.56 ft w x 65.62 ft l	2.00 m w x 20.00 m l
Surface Par Rouleau	47.84 sy/roll	40 sq m/roll
Poids Par Rouleau	229.28 lbs	104 kg



Méthodes d'Installation Conseillées



Coordination Des Produits

Sheet: Traction Aqua

performance + Tests et essai

résistance à la chaleur (ASTM F1514)	Passes
résistance à la lumière (ASTM F1515)	Passes
résistance chimique (ASTM F925)	Passes
densité de fumée (ASTM E662, mode flamme)	Passes
Essai au panneau radiant (Astm E648)	Passes, Class I
coefficient de frottement (ASTM D2407, résistance au glissement)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces
Enhanced Slip Resistance / Surface Roughness	20
Enhanced Slip Resistance / AS 4586 Appendix D	R11
Enhanced Slip Resistance / DIN 51130/EN 16165 Annex B	R11
Enhanced Slip Resistance / AS 4586 Appendix A	P4
Enhanced Slip Resistance / RRL Pendulum Test	45+
Enhanced Slip Resistance / EN 13845	ESf

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garanties

[10 Year Commercial Limited](#)
[Commercial Limited Underbed Bond Warranty S150/4151/Lokworx+ Resilient](#)

Attributs + Certifications

Health & Wellbeing

Material Ingredient Transparency
Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure
FloorScore® | Agréé

Climate Impact

Environmental Product Declaration (EPD)
Total Recycled Content

3rd Party Certified in Accordance to ISO 14044 And 14071
0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

Country of Origin | Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Réduction des matières dangereuses Partie 1 : Optimisation des limites des matières dangereuses – 1 pt	Absence of Heavy Metals
X10 Réduction des composés volatils Partie 1 (A) : Gérer l'optimisation des composés organiques volatils (COV) - 1 pt	Absence of Halogenated Flame Retardants
Partie 2 : Gérer l'optimisation des composés organiques semi-volatils (COSV) - 1 pt	Ortho-Phthalates
X11 Contrôle des émissions à long terme Partie 2 : Optimisation des revêtements de sol – 1 pt	FloorScore Certificate

Contribution Au Certificat Vert Leed

Crédit EQ : matériaux faibles émissions

[Installation Guidelines](#)
[Maintenance Guidelines](#)

FloorScore Certified


Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.


Visit shawcontract.com/testing for more information.

Available Colorways

					
Share 00104 Weldrod 25202	Dash 00114 Weldrod 25221	Nurture 00130 Weldrod 25212	Mettle 00240 Weldrod 25213	Sustain 00515 Weldrod 29858	Prosper 00518 Weldrod 25764



Encourage 00535
Weldrod 25233



Abundance 00740
Weldrod 25204

