

## Traction Sole


Coleção	<b>Tractionsafety</b>	
Número Do Produto	<b>4492V</b>	
Número Do Estilo Da Haste De Soldagem	<b>184CA</b>	
classe		
Acabamento	<b>ExoGuard®</b>	
	U.s.	Metric
Espessura Total Do Produto	<b>0.079 in</b>	<b>2 mm</b>
Installation Type	<b>Dry Back</b>	
Instalação	<b>Direct Glue</b>	
Adesivo Recomendado	<b>S150-95 Resilient Tile Spray Adhesive, 4200 1G Resilient Sheet Adhesive, 4200 Resilient Sheet 4 Gallon, 2200 4G Resilient Sheet Adhesive or 4151 Multi-Use Premium 4 Gallon</b>	

### Empacotamento

Tamanho Real Do Rolo	<b>6.56 ft w x 65.62 ft l</b>	<b>2.00 m w x 20.00 m l</b>
Área Por Rolo	<b>47.84 sy/roll</b>	<b>40 sq m/roll</b>
Peso Por Rolo	<b>229.28 lbs</b>	<b>104 kg</b>



### Método De Instalação Recomendado



Reverso

### Produtos Coordenados

Sheet: Traction Aqua

### desempenho + teste

resistência ao calor (ASTM F1514)	<b>Passes</b>
resistência à luz (ASTM F1515)	<b>Passes</b>
resistência a produtos químicos (ASTM F925)	<b>Passes</b>
densidade de fumaça (ASTM E662, modo flamejante)	<b>Passes</b>
painel radiante (ASTM E648)	<b>Passes, Class I</b>
coeficiente de atrito (ASTM D2407, resistência ao deslizamento)	<b>≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces</b>
Enhanced Slip Resistance / Surface Roughness	<b>20</b>
Enhanced Slip Resistance / AS 4586 Appendix D	<b>R11</b>
Enhanced Slip Resistance / DIN 51130/EN 16165 Annex B	<b>R11</b>
Enhanced Slip Resistance / AS 4586 Appendix A	<b>P4</b>
Enhanced Slip Resistance / RRL Pendulum Test	<b>45+</b>
Enhanced Slip Resistance / EN 13845	<b>ESf</b>

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Corporate Headquarters +1 800 257 7429 | +1 706 532 7984 | Atlanta +1 404 853 7429 | Bengaluru +91 80 6773 0202 | Beijing +86 10 6568 588 | Chicago +1 312 467 1331 | Dubai +971 4 584 6956 | Hong Kong +852 2623 0371 | London +44 207 961 4120 | Los Angeles +1 800 233 1614 | Melbourne +61 3 9939 8543 | Mexico City +55 5010 7600 | Mumbai +91 22 6284 5050 | Nantong +86 400 800 7429 | New York +1 212 953 7429 | Paris +33 (0) 1 81 22 44 39 | San Francisco +1 415 955 1920 | Shanghai +86 21 3338 4000 | Singapore +65 6733 1811 | Sydney +61 800 556 302

Garantias

[10 Year Commercial Limited](#)  
[Commercial Limited Underbed Bond Warranty S150/4151/Lokworx+ Resilient](#)

Atributos + Certificações

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD)   1000 ppm Disclosure
Indoor Air Quality	FloorScore®   Certificado
Climate Impact	
Environmental Product Declaration (EPD)	3rd Party Certified in Accordance to ISO 14044 And 14071
Total Recycled Content	0% (Pre-Consumer 0%   Post-Consumer 0%)
Global Product Assessment	Country of Origin   Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	<b>Absence of Asbestos</b>
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	<b>Absence of Heavy Metals</b>
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	<b>Absence of Halogenated Flame Retardants</b>
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	<b>Ortho-Phthalates</b>
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	<b>FloorScore Certificate</b>

Crédito De Contribuição

Crédito de EQ: Materiais de baixa emissão	<b>FloorScore® Certified</b>
Opção 1: cálculos de categoria de produto	
<a href="#">Installation Guidelines</a>	Please visit <a href="http://www.shawcontract.com">www.shawcontract.com</a> for the most current warranty information.
<a href="#">Maintenance Guidelines</a>	Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.
	This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
	Visit <a href="http://shawcontract.com/testing">shawcontract.com/testing</a> for more information.

Available Colorways

					
Share 00104 Weldrod 25202	Dash 00114 Weldrod 25221	Nurture 00130 Weldrod 25212	Mettle 00240 Weldrod 25213	Sustain 00515 Weldrod 29858	Prosper 00518 Weldrod 25764

