

Traction Aqua


Collection	Tractionsafety	
Style Number	4493V	
Welding Rod Style Number	184CA	
class		
Finish	ExoGuard®	
	U.s.	Metric
Overall Product Thickness	0.079 in	2 mm
Installation Type	Dry Back	
Installation	Direct Glue	
Recommended Adhesive	S150 Resilient Tile, 4200 1G Resilient Sheet, 4200 Resilient Sheet 4 Gallon, Weld Rod 320', 2200 4G Resilient Sheet or 4151Multi-Use Premium 4 Gallon	

Packaging

Actual Roll Size	6.56 ft w x 65.62 ft l	2.00 m w x 20.00 m l
Area Per Roll	47.84 sy/roll	40 sq m/roll
Weight Per Roll	238.09 lbs	108 kg



Recommended Installation Method



Coordinating Products

Sheet: Traction Sole

performance + testing

resistance to heat (ASTM F1514)	Passes
resistance to light (ASTM F1515)	Passes
resistance to chemicals (ASTM F925)	Passes
smoke density (ASTM E662, flaming mode)	Passes
radiant panel (ASTM E648)	Passes, Class I
coefficient of friction (ASTM D2407, slip resistance)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces
Enhanced Slip Resistance / AS 4586 Appendix D	R11
Enhanced Slip Resistance / DIN 51130/EN 16165 Annex B	R11
Enhanced Slip Resistance / AS 4586 Appendix A	P4
Enhanced Slip Resistance / RRL Pendulum Test	50+
Enhanced Slip Resistance / EN 13845	ESf
Enhanced Slip Resistance / Surface Roughness	20

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

[Commercial Limited Underbed Bond Warranty S150/4151/Lokworx+ Resilient](#)
[10 Year Commercial Limited](#)

Attributes + Certifications

Health & Wellbeing

Material Ingredient Transparency
Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure
FloorScore® | Certified

Climate Impact

Environmental Product Declaration (EPD)
Total Recycled Content

3rd Party Certified in Accordance to ISO 14044 And 14071
0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

Country of Origin | Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt

Absence of Asbestos
Absence of Heavy Metals
Absence of Halogenated Flame Retardants

Ortho-Phthalates
FloorScore Certificate

Green Leed Contribution Credit

EQ Credit: Low Emitting Materials
Option 1: Product Category Calculations

FloorScore® Certified







[Installation Guidelines](#)
[Maintenance Guidelines](#)

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways

					
Share 00104 Weldrod 25202	Dash 00114 Weldrod 25772	Nurture 00130 Weldrod 25212	Assist 00496 Weldrod 24490	Prosper 00518 Weldrod 25764	Goodness 00761 Weldrod 25762

