

Traction Aqua


Coleção	Tractionsafety	
Número Do Produto	4493V	
Número Do Estilo Da Haste De Soldagem	184CA	
classe		
Acabamento	ExoGuard®	
	U.s.	Metric
Espessura Total Do Produto	0.079 in	2 mm
Installation Type	Dry Back	
Instalação	Direct Glue	
Adesivo Recomendado	S150 Resilient Tile, 4200 1G Resilient Sheet, 4200 Resilient Sheet 4 Gallon, Weld Rod 320', 2200 4G Resilient Sheet or 4151Multi-Use Premium 4 Gallon	

Empacotamento

Tamanho Real Do Rolo	6.56 ft w x 65.62 ft l	2.00 m w x 20.00 m l
Área Por Rolo	47.84 sy/roll	40 sq m/roll
Peso Por Rolo	238.09 lbs	108 kg



Método De Instalação Recomendado



Reverso

Produtos Coordenados

Sheet: Traction Sole

desempenho + teste

resistência ao calor (ASTM F1514)	Passes
resistência à luz (ASTM F1515)	Passes
resistência a produtos químicos (ASTM F925)	Passes
densidade de fumaça (ASTM E662, modo flamejante)	Passes
painel radiante (ASTM E648)	Passes, Class I
coeficiente de atrito (ASTM D2407, resistência ao deslizamento)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces
Enhanced Slip Resistance / AS 4586 Appendix D	R11
Enhanced Slip Resistance / DIN 51130/EN 16165 Annex B	R11
Enhanced Slip Resistance / AS 4586 Appendix A	P4
Enhanced Slip Resistance / RRL Pendulum Test	50+
Enhanced Slip Resistance / EN 13845	ESf
Enhanced Slip Resistance / Surface Roughness	20

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Corporate Headquarters +1 800 257 7429 | +1 706 532 7984 | Atlanta +1 404 853 7429 | Bengaluru +91 80 6773 0202 | Beijing +86 10 6568 588 | Chicago +1 312 467 1331 | Dubai +971 4 584 6956 | Hong Kong +852 2623 0371 | London +44 207 961 4120 | Los Angeles +1 800 233 1614 | Melbourne +61 3 9939 8543 | Mexico City +55 5010 7600 | Mumbai +91 22 6284 5050 | Nantong +86 400 800 7429 | New York +1 212 953 7429 | Paris +33 (0) 1 81 22 44 39 | San Francisco +1 415 955 1920 | Shanghai +86 21 3338 4000 | Singapore +65 6733 1811 | Sydney +61 800 556 302

Garantias

[10 Year Commercial Limited](#)
[Commercial Limited Underbed Bond Warranty S150/4151/Lokworx+ Resilient](#)

Atributos + Certificações

Health & Wellbeing

Material Ingredient Transparency
Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure
FloorScore® | Certificado

Climate Impact

Environmental Product Declaration (EPD)
Total Recycled Content

3rd Party Certified in Accordance to ISO 14044 And 14071
0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

Country of Origin | Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt

Absence of Asbestos
Absence of Heavy Metals
Absence of Halogenated Flame Retardants

Ortho-Phthalates
FloorScore Certificate

Crédito De Contribuição







Crédito de EQ: Materiais de baixa emissão
Opção 1: cálculos de categoria de produto

FloorScore® Certified

[Installation Guidelines](#)
[Maintenance Guidelines](#)

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.
This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
Visit shawcontract.com/testing for more information.

Available Colorways

					
Share 00104 Weldrod 25202	Dash 00114 Weldrod 25772	Nurture 00130 Weldrod 25212	Assist 00496 Weldrod 24490	Prosper 00518 Weldrod 25764	Goodness 00761 Weldrod 25762

