

Pivot

| | | |
|----------------------|--|--------------------------|
| Collection | Art + Science | |
| Style Number | 4499V | |
| Construction | Heavy Commercial Pvc-Free Ecoworx Resilient | |
| Finish | ExoGuard+® | |
| | U.S. | Metric |
| Nominal Dimensions | 8 in w x 51 in l | 21 cm w x 129 cm l |
| Actual Dimensions | 8.27 in w x 50.79 in l | 21.01 cm w x 129.01 cm l |
| Overall Thickness | 0.098 in | 2.5 mm |
| Edge Profile | Micro-Bevel | |
| Installation Type | Dry Back | |
| Recommended Adhesive | 4200 Resilient Adhesive (1 gal) or 4200 Resilient Adhesive (4 gal) | |

Packaging

| | | |
|-------------------|-------------|-----------|
| Pieces per Carton | 16 pcs | |
| Area per Carton | 46.65 sq ft | 4.33 sq m |
| Weight per Carton | 36.431 lbs | 16.52 kg |



Recommended Installation Method



Coordinating Products

PVC-Free: Observe

Performance + Testing

| | | | |
|--|---|--|--|
| Static Load (ASTM F970) | Passes (Modified), *2500 lbs | *This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary. | |
| Resistance to Heat (ASTM F1514) | Passes | | |
| Resistance to Light (ASTM F1515) | Passes | | |
| Resistance to Chemicals (ASTM F925) | Passes | | |
| Radiant Panel (ASTM E648) | Passes, Class I | | |
| Coefficient of Friction (ASTM D2047, Slip Resistance) | >0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes | | |
| Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number. | | | |

Warranties

- [1 Year Commercial Limited Warranty](#)
- [25 Year Commercial System Warranty](#)

Material Health & Environmental Certifications

| | |
|----------------------------------|---|
| Health & Wellbeing | |
| Material Ingredient Transparency | Greenhealth Approved Yes Health Product Declaration (HPD) 1000 ppm Disclosure Declare LBC Compliant |
| Climate Impact | |
| Embodied Carbon (Cradle to Gate) | 5.2 Kg Co ₂ /M ² |
| Life-Cycle Carbon Emissions | Carbon Neutral |
| Total Recycled Content | 25% (Pre-Consumer 0% Post-Consumer 25%) |
| Global Product Assessment | Environmental Guarantee* Through Our Environmental Guarantee, Shaw Pledges to Transport And Recycle Any Ecoworx Resilient Within The United States And Canada At No Cost to The Customer. Country of Origin Imported |

WELL V2 Contribution Credit

| | |
|--|---|
| X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition | Absence of Asbestos |
| X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization | Absence of Heavy Metals |
| X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization | Absence of Halogenated Flame Retardants |
| X10 Volatile Compound Reduction Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization | Ortho-Phthalates Free |
| X11 Long Term Emissions Control Part 2: Flooring Optimization | Green Guard Gold Certified |
| X14 Material Transparency Part 1: Promote Ingredient Disclosure Optimization | Health Product Declaration (HPD) 1000 Ppm Disclosure |

Leed v4 Contribution Credits

| | |
|---|---|
| MR Credit: Building Product Disclosure and Optimization Material Ingredients - Option 1: Material Ingredient Reporting | Health Product Declaration (HPD) 1000 Ppm Disclosure |
|---|---|

Additional Information

* To learn more about the recyclability of our products and our Environmental Guarantee, please visit [shawcontract.com/sustainability](#).

[Installation Guidelines](#)

[Maintenance](#)

Please visit [www.shawcontract.com](#) for the most current warranty information.

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](#) for more information.

Available Colorways



Reform 00111
V3 - Moderate Variation



Mindset 00115
V2 - Slight Variation



Reclaim 00121
V2 - Slight Variation



Climate 00125
V2 - Slight Variation



Reuse 00140
V2 - Slight Variation



Value 00144
V3 - Moderate Variation



Renew 00155
V3 - Moderate Variation



New Growth 00240
V2 - Slight Variation



Change 00504
V4 - Substantial Variation



Resilience 00570
V3 - Moderate Variation



Process 00575
V2 - Slight Variation



Native 00720
V2 - Slight Variation



Ecology 00730
V2 - Slight Variation



Earthen 00740
V3 - Moderate Variation



Future 00750
V2 - Slight Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

