

Pivot


Collection	Art + Science	
Style Number	4499V	
Construction	Heavy Commercial Pvc-Free Ecoworx Resilient	
Finish	ExoGuard+®	
	U.S.	Metric
Nominal Dimensions	8 in w x 51 in l	21 cm w x 129 cm l
Actual Dimensions	8.27 in w x 50.79 in l	21.01 cm w x 129.01 cm l
Overall Thickness	0.098 in	2.5 mm
Edge Profile	Micro-Bevel	
Installation Type	Dry Back	
Recommended Adhesive	4200 Resilient Adhesive (1 gal) or 4200 Resilient Adhesive (4 gal)	

Packaging

Pieces per Carton	16 pcs	
Area per Carton	46.65 sq ft	4.33 sq m
Weight per Carton	36.431 lbs	16.52 kg



Recommended Installation Method



Coordinating Products

PVC-Free: Observe

Performance + Testing

Static Load (ASTM F970)	Passes (Modified), *2500 lbs	*This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary.	
Resistance to Heat (ASTM F1514)	Passes		
Resistance to Light (ASTM F1515)	Passes		
Resistance to Chemicals (ASTM F925)	Passes		
Radiant Panel (ASTM E648)	Passes, Class I		
Coefficient of Friction (ASTM D2047, Slip Resistance)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes		
Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.			

Warranties

- [1 Year Commercial Limited Warranty](#)
- [25 Year Commercial System Warranty](#)

Material Health & Environmental Certifications

Health & Wellbeing	
Material Ingredient Transparency	Greenhealth Approved Yes Health Product Declaration (HPD) 1000 ppm Disclosure Declare LBC Compliant
Climate Impact	
Embodied Carbon (Cradle to Gate)	5.2 Kg Co ₂ /M ²
Life-Cycle Carbon Emissions	Carbon Neutral
Total Recycled Content	25% (Pre-Consumer 0% Post-Consumer 25%)
Global Product Assessment	Environmental Guarantee* Through Our Environmental Guarantee, Shaw Pledges to Transport And Recycle Any Ecoworx Resilient Within The United States And Canada At No Cost to The Customer. Country of Origin Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization	Absence of Heavy Metals
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization	Absence of Halogenated Flame Retardants
X10 Volatile Compound Reduction Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization	Ortho-Phthalates Free
X11 Long Term Emissions Control Part 2: Flooring Optimization	Green Guard Gold Certified
X14 Material Transparency Part 1: Promote Ingredient Disclosure Optimization	Health Product Declaration (HPD) 1000 Ppm Disclosure

Leed v4 Contribution Credits

MR Credit: Building Product Disclosure and Optimization Material Ingredients - Option 1: Material Ingredient Reporting	Health Product Declaration (HPD) 1000 Ppm Disclosure
---	---

Additional Information

* To learn more about the recyclability of our products and our Environmental Guarantee, please visit [shawcontract.com/sustainability](#).

[Installation Guidelines](#)

[Maintenance](#)

Please visit [www.shawcontract.com](#) for the most current warranty information.

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](#) for more information.

Available Colorways

 Reform 00111 V3 - Moderate Variation	 Mindset 00115 V2 - Slight Variation	 Reclaim 00121 V2 - Slight Variation	 Climate 00125 V2 - Slight Variation	 Reuse 00140 V2 - Slight Variation	 Value 00144 V3 - Moderate Variation
 Renew 00155 V3 - Moderate Variation	 New Growth 00240 V2 - Slight Variation	 Change 00504 V4 - Substantial Variation	 Resilience 00570 V3 - Moderate Variation	 Process 00575 V2 - Slight Variation	 Native 00720 V2 - Slight Variation
 Ecology 00730 V2 - Slight Variation	 Earthen 00740 V3 - Moderate Variation	 Future 00750 V2 - Slight Variation			

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

