

Pivot

Numéro Du Style	4499V	
Type De Produit	Heavy Commercial Pvc-Free Ecoworx™ Resilient	
Collection	Art + Science	
Construction	Standard	Données + Performance
Type of Floorcovering	EN 1307	EcoWorx resilient
Classification	ISO 10874	class 34 very heavy commercial use
Poids Total	EN ISO 23997	3.49 kg/m²
Epaisseur Du Velours	EN ISO 24346	2.5 mm
Dimensions	EN 994	21.01 cm x 129.01 cm 16 tiles (4.33 sq m) per box
Poids Par Carton		16.52 kg




Performance

Inflamabilité	EN 13501-1	Bfl-S1
Résistance Thermique m ² K/w	ISO 8302	0.013 m² K/W
Capacités Antidérapantes	BS 7976-2	Woodgrain Emboss: PTV Dry 58 PTV Wet 52 (pendulum)
	DIN 51130	R10
Stabilité Dimensionnelle	EN ISO 23999	≤0.15%
Chaise À Roulette	EN 425, ISO 4918	no damage
Impact Sound Reduction	BS EN ISO 10140	ΔLw 9dB/20dB with 2mm underlay
Résistance De La Couleur À La Lumière	BS EN ISO 105-BO2	8

15 Year Commercial Limited System Warranty subject to installation in full accordance with the manufacturer's instructions and a regular effective cleaning and maintenance programme. Second location warranties are available with the use of non-adhesive IOBAC Magtabs and Tabit accessories.



Méthodes d'Installation Conseillées



Coordination Des Produits

PVC-Free: Observe

colour and visual variation index



ΔLw 9dB/20dB with 2mm underlay

Corporate Headquarters +1 800 257 7429 | +1 706 532 7984 | Atlanta +1 404 853 7429 | Bengaluru +91 80 6773 0202 | Beijing +86 10 6568 588 | Chicago +1 312 467 1331 | Dubai +971 4 584 6956 | Hong Kong +852 2623 0371 | London +44 207 961 4120 | Los Angeles +1 800 233 1614 | Melbourne +61 3 9939 8543 | Mexico City +55 5010 7600 | Mumbai +91 22 6284 5050 | Nantong +86 400 800 7429 | New York +1 212 953 7429 | Paris +33 (0) 1 81 22 44 39 | San Francisco +1 415 955 1920 | Shanghai +86 21 3338 4000 | Singapore +65 6733 1811 | Sydney +61 800 556 302

© 2025 Shaw Industries Group, Inc., a Berkshire Hathaway Company
July 19, 2025

Attributs + Certifications

Greenhealth Approved

Déclaration sanitaire de produit (HPD)

Déclaration environnementale de produit (EPD)

Embodied Carbon (Cradle to Gate)

Life-Cycle Carbon Emissions

Déclarer

Environmental Guarantee

Greenguard Gold

Total Recycled Content

pays d'origine

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition

X08 Réduction des matières dangereuses Partie 1 : Optimiser la limitation des matières dangereuses – 1 pt

X10 Réduction des composés volatils Partie 1 (A) : Optimisation de la gestion des composés organiques volatils (COV) – 1 pt

Part 2 : Optimisation de la gestion des composés organiques semi-volatils (COSV) – 1 pt

X11 Contrôle des émissions à long terme Partie 2 : Optimisation des revêtements de sol – 1 pt

X14 Transparence des matériaux Partie 1 : Promouvoir l'optimisation de la divulgation des composants – max 2 pts

Contribution À La Certification Leed

MR Credit: Building Product Disclosure and Optimisation

Material Ingredients - Option 1: Material Ingredient Reporting

"Crédit EQ : matériaux faibles émissions

Option 1 : calculs par catégorie de produit"

Informations Supplémentaires

* To learn more about the recyclability of our products and our Environmental Guarantee, please visit shawcontract.com/sustainability.

**Meets or exceeds all local and national regulations in country of manufacture.

[Installation](#)[Maintenance](#)[Yes](#)[1000 ppm Disclosure](#)[3rd Party Certified in Accordance with ISO 14025, EN 15804, And ISO 21930](#)5.2 Kg Co₂/M²

Carbon Neutral

[LBC Compliant](#)[Environmental Guarantee* | Through Our Environmental Guarantee, Shaw Pledges to Transport And Recycle Any Ecoworx Resilient Within The United States And Canada At No Cost to The Customer.](#)

Certifié

25% (Pre-Consumer 0% | Post-Consumer 25%)

Allemagne

Absence of Asbestos

Absence of Heavy Metals

Absence of Halogenated Flame Retardants

Ortho-Phthalates Free

Green Guard Gold Certified

Health Product Declaration (HPD) | 1000 Ppm Disclosure

Health Product Declaration (HPD) | 1000 Ppm Disclosure

Greenguard Gold Certified

Please visit www.shawcontract.com for the most current warranty information.

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

*****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit shawcontract.com/testing for more information.

Indice De Réflexion Lumineuse

 <div>Reform 00111 LRV 33.0 L* 64.13 V3 - Moderate Variation</div>	 <div>Mindset 00115 LRV 41.4 L* 70.46 V2 - Slight Variation</div>	 <div>Reclaim 00121 LRV 29.5 L* 61.24 V2 - Slight Variation</div>	 <div>Climate 00125 LRV 25.4 L* 57.42 V2 - Slight Variation</div>	 <div>Reuse 00140 LRV 38.5 L* 68.38 V2 - Slight Variation</div>	 <div>Value 00144 LRV 41.8 L* 70.76 V3 - Moderate Variation</div>
 <div>Renew 00155 LRV 23.6 L* 55.70 V3 - Moderate Variation</div>	 <div>New Growth 00240 LRV 27.1 L* 59.07 V2 - Slight Variation</div>	 <div>Change 00504 LRV 43.7 L* 72.03 V4 - Substantial Variation</div>	 <div>Resilience 00570 LRV 13.1 L* 42.95 V3 - Moderate Variation</div>	 <div>Process 00575 LRV 16.4 L* 47.45 V2 - Slight Variation</div>	 <div>Native 00720 LRV 21.8 L* 53.81 V2 - Slight Variation</div>
 <div>Ecology 00730 LRV 20.2 L* 52.05 V2 - Slight Variation</div>	 <div>Earthen 00740 LRV 14.1 L* 44.39 V3 - Moderate Variation</div>	 <div>Future 00750 LRV 15.3 L* 45.98 V2 - Slight Variation</div>			

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

