


Pivot


Collection	Art + Science	
Style Number	4499V	
Construction	Heavy Commercial Pvc-Free Ecoworx Resilient	
Finish	ExoGuard+®	
	U.S.	Metric
Nominal Dimensions	8 in w x 51 in l	21 cm w x 129 cm l
Actual Dimensions	8.27 in w x 50.79 in l	21.01 cm w x 129.01 cm l
Overall Thickness	0.098 in	2.5 mm
Edge Profile	Micro-Bevel	
Installation Type	Dry Back	
Installation	Direct Glue	
Recommended Adhesive	4200 Resilient 1 Gallon or 4200 Resilient 4 Gallon	



Packaging

Pieces per Carton	16 pcs	
Area per Carton	46.65 sq ft	4.33 sq m
Weight per Carton	36.431 lbs	16.52 kg

Recommended Installation Method



Coordinating Products

PVC-Free: Observe, Experiment

Performance + Testing

Static Load (ASTM F970)

Passes (Modified), *2500 lbs

*This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary.

Resistance to Heat (ASTM F1514)

Passes

Resistance to Light (ASTM F1515)

Passes

Resistance to Chemicals (ASTM F925)

Passes

Radiant Panel (ASTM E648)

Passes, Class I

Coefficient of Friction (ASTM D2047, Slip Resistance)

>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

[1 Year Commercial Limited Warranty](#)

[25 Year Commercial System Warranty](#)

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Material Health & Environmental Certifications

Health & Wellbeing

Material Ingredient Transparency

Greenhealth Approved | Yes
Health Product Declaration (HPD) | 1000 ppm Disclosure
Declare | LBC Compliant

Climate Impact

Environmental Product Declaration (EPD)

in Accordance with ISO 14025:2006 And EN 15804:2012+a2:2019/Ac:2021

Embodied Carbon (Cradle to Gate)

5.2 Kg Co₂/M²

Life-Cycle Carbon Emissions

Carbon Neutral

Total Recycled Content

25% (Pre-Consumer 0% | Post-Consumer 25%)

Global Product Assessment

Environmental Guarantee* | Through Our Environmental Guarantee, Shaw Pledges to Transport And Recycle Any Ecoworx Resilient Within The United States And Canada At No Cost to The Customer.

GSA | Approved

Country of Origin | Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions

Part 1: (C): Restrict Asbestos Precondition

Absence of Asbestos

X08 Hazardous Material Reduction

Part 1: Limit Hazardous Materials Optimization

Absence of Heavy Metals

X10 Volatile Compound Reduction

Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization

Absence of Halogenated Flame Retardants

X10 Volatile Compound Reduction

Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization

Ortho-Phthalates Free

X11 Long Term Emissions Control

Part 2: Flooring Optimization

Green Guard Gold Certified

X14 Material Transparency

Part 1: Promote Ingredient Disclosure Optimization

Health Product Declaration (HPD) | 1000 Ppm Disclosure

Leed v4 Contribution Credits

MR Credit: Building Product Disclosure and Optimization
Material Ingredients - Option 1: Material Ingredient Reporting

Health Product Declaration (HPD) | 1000 Ppm Disclosure

Additional Information

* To learn more about the recyclability of our products and our Environmental Guarantee, please visit shawcontract.com/sustainability.

**Meets or exceeds all local and national regulations in country of manufacture.

[Installation](#)

[Maintenance](#)

Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit shawcontract.com/testing for more information.

Available Colorways

					
Reform 00111 LRV 33.0 L* 64.13 V3 - Moderate Variation	Mindset 00115 LRV 41.4 L* 70.46 V2 - Slight Variation	Reclaim 00121 LRV 29.5 L* 61.24 V2 - Slight Variation	Climate 00125 LRV 25.4 L* 57.42 V2 - Slight Variation	Reuse 00140 LRV 38.5 L* 68.38 V2 - Slight Variation	Value 00144 LRV 41.8 L* 70.76 V3 - Moderate Variation
					
Renew 00155 LRV 23.6 L* 55.70 V3 - Moderate Variation	New Growth 00240 LRV 27.1 L* 59.07 V2 - Slight Variation	Change 00504 LRV 43.7 L* 72.03 V4 - Substantial Variation	Resilience 00570 LRV 13.1 L* 42.95 V3 - Moderate Variation	Process 00575 LRV 16.4 L* 47.45 V2 - Slight Variation	Native 00720 LRV 21.8 L* 53.81 V2 - Slight Variation
					
Ecology 00730 LRV 20.2 L* 52.05 V2 - Slight Variation	Earthen 00740 LRV 14.1 L* 44.39 V3 - Moderate Variation	Future 00750 LRV 15.3 L* 45.98 V2 - Slight Variation			

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

