

Inhabit Plus Sheet

Collection	Abide & Inhabit	
Style Number	4487V	
Welding Rod Style Number	353VS	
Construction	Commercial Heterogeneous Sheet With Fibreglass	
Finish	ExoGuard+®	
	U.s.	Metric
Wear Layer Thickness	20 mil (0.02 in)	0.51 mm
Overall Thickness	0.087 in	2.2 mm
Installation Type	Dry Back	
Installation	Direct Glue	
Recommended Adhesive	S150 Resilient Sheet Spray 1 Can, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail or 4151	

Packaging

Actual Roll Size	6.56 ft w x 65.60 ft l	2.00 m w x 19.99 m l
Area Per Roll	47.87 sy/roll	40.03 sq m/roll
Weight Per Roll	323.15 lbs	146.58 kg



Recommended Installation Method



Reverse

Coordinating Products

Sheet: Inhabit Sheet

LVT: Abide

Performance + Testing

Static Load (ASTM F970)	Passes (Modified), *1500 lbs	*This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary.
Flexibility (ASTM F137)	Passes	
Resistance to Heat (ASTM F1514)	Passes	
Resistance to Light (ASTM F1515)	Passes	
Resistance to Chemicals (ASTM F925)	Passes	
Radiant Panel (ASTM E648)	Passes, Class I	
coefficient of friction (ASTM D2407, slip resistance)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces	

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

[15 Year Commercial Limited](#)
[Commercial Limited Underbed Bond Warranty S150/4151/Lokworx+ Resilient](#)

















Material Health & Environmental Certifications

Health & Wellbeing	
Indoor Air Quality	FloorScore® Certified
Climate Impact	
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	Country of Origin Imported

Green Leed Contribution Credit

EQ Credit: Low Emitting Materials	FloorScore® Certified
Option 1: Product Category Calculations	
Installation Guidelines	Please visit www.shawcontract.com for the most current warranty information.
Maintenance Guidelines	Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.
	This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
	Visit shawcontract.com/testing for more information.

Available Colorways

					
Oyster Shell Oak 87140 V3 - Moderate Variation	Antique Oak 87150 V3 - Moderate Variation	Grain Wenge 87210 V2 - Slight Variation	 Barley Oak 87220 V3 - Moderate Variation	Sesame Oak 87240 V3 - Moderate Variation	 Honey Wenge 87250 V2 - Slight Variation
					
Palladium Oak 87515 V3 - Moderate Variation	 Liquorice Oak 87570 V4 - Substantial Variation	Ginger Oak 87630 V4 - Substantial Variation	Buckskin Oak 87660 V3 - Moderate Variation	 Nubuck Oak 87700 V4 - Substantial Variation	Clove Walnut 87710 V3 - Moderate Variation



 **Quick Ship** Immediately - In Stock Australia

Color and Visual Variation Index
Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

