

Inhabit Plus Sheet

|                          |   |         |
|--------------------------|---|---------|
| Collection               | Abide & Inhabit   |         |
| Style Number             | 4487V   |         |
| Welding Rod Style Number | 353VS   |         |
| Construction             | Commercial Heterogeneous Sheet With Fibreglass  |         |
| Finish                   | ExoGuard+®  |         |
|                          | U.s.  | Metric  |
| Wear Layer Thickness     | 20 mil (0.02 in)  | 0.51 mm |
| Overall Thickness        | 0.087 in  | 2.2 mm  |
| Installation Type        | Dry Back  |         |
| Installation             | Direct Glue   |         |
| Recommended Adhesive     | S150 Resilient Sheet Spray 1 Can, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail or 4151 |         |

Packaging

|                  |                        |                      |
|------------------|------------------------|----------------------|
| Actual Roll Size | 6.56 ft w x 65.60 ft l | 2.00 m w x 19.99 m l |
| Area Per Roll    | 47.87 sy/roll          | 40.03 sq m/roll      |
| Weight Per Roll  | 323.15 lbs             | 146.58 kg            |



Recommended Installation Method



Coordinating Products

LVT: Abide  
Sheet: Inhabit Sheet

Performance + Testing

|   |   |  |
|---|---|--|
| Static Load (Astm F970)                               | Passes (Modified), *1500 lbs  | *This Test Is Intended To Compare Relative Properties Of Different Styles And Constructions. Results Are Based On A Laboratory Test And Used For Comparative Purposes - Real Life Load Limit May Vary. |
| Flexibility (Astm F137)                               | Passes  |  |
| Resistance To Heat (Astm F1514)                       | Passes  |  |
| Resistance To Light (Astm F1515)                      | Passes  |  |
| Resistance To Chemicals (Astm F925)                   | Passes  |  |
| Radiant Panel (Astm E648)                             | Passes, Class I   |  |
| Coefficient Of Friction (Astm D2407, Slip Resistance) | ≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces |  |

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

15 Year Commercial Limited  
[Commercial Limited Underbed Bond Warranty S150/4151/Lokworx+ Resilient](#)

Material Health & Environmental Certifications

|                           |   |
|---------------------------|---|
| Health & Wellbeing        |   |
| Indoor Air Quality        | FloorScore®   Certified                 |
| Climate Impact            |   |
| Total Recycled Content    | 0% (Pre-Consumer 0%   Post-Consumer 0%) |
| Global Product Assessment |   |
|                           | Country of Origin   Imported            |

Green Leed Contribution Credit

EQ Credit: Low Emitting Materials  
Option 1: Product Category Calculations

Installation Guidelines  
Maintenance Guidelines

FloorScore Certified


Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.


\*\*\*\*\*Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.


Available Colorways




Oyster Shell Oak 87140  
V3 - Moderate Variation




Antique Oak 87150  
V3 - Moderate Variation




Grain Wenge 87210  
V2 - Slight Variation




Barley Oak 87220  
V3 - Moderate Variation




Sesame Oak 87240  
V3 - Moderate Variation




Honey Wenge 87250  
V2 - Slight Variation




Palladium Oak 87515  
V3 - Moderate Variation




Liquorice Oak 87570  
V4 - Substantial Variation




Ginger Oak 87630  
V4 - Substantial Variation



Buckskin Oak 87660  
V3 - Moderate Variation



Nubuck Oak 87700  
V4 - Substantial Variation



Clove Walnut 87710  
V3 - Moderate Variation



Cocoa Walnut 87760  
V3 - Moderate Variation

Sable Oak 87780  
V3 - Moderate Variation

 **Quick Ship** 4 weeks

**Color and Visual Variation Index**

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

