

Inhabit Plus Sheet

Collection	Abide & Inhabit	
Style Number	4487V	
Welding Rod Style Number	353VS	
Construction	Commercial Heterogeneous Sheet With Fibreglass	
Finish	ExoGuard+®	
	U.s.	Metric
Wear Layer Thickness	20 mil (0.02 in)	0.51 mm
Overall Thickness	0.087 in	2.2 mm
Installation Type	Dry Back	
Installation	Direct Glue	
Recommended Adhesive	S150 Resilient Sheet Spray 1 Can, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Resilient Tile 4 Gallon or 4151	

Packaging

Actual Roll Size	6.56 ft w x 65.60 ft l	2.00 m w x 19.99 m l
Area Per Roll	47.87 sy/roll	40.03 sq m/roll
Weight Per Roll	323.15 lbs	146.58 kg



Recommended Installation Method



Reverse

Coordinating Products

LVT: Abide

Sheet: Inhabit Sheet

Performance + Testing

Flexibility (Astm F137)	Passes
Resistance To Heat (Astm F1514)	Passes
Resistance To Light (Astm F1515)	Passes
Resistance To Chemicals (Astm F925)	Passes
Coefficient Of Friction (Astm D2407, Slip Resistance)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

15 Year Commercial Limited  
[Commercial Limited Underbed Bond Warranty S150/4151/Lokworx+ Resilient](#)

Material Health & Environmental Certifications

Climate Impact

Total Recycled Content0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

FloorScore® | Certified

Country of Origin | Imported

Green Leed Contribution Credit

EQ Credit: Low Emitting Materials  
Option 1: Product Category Calculations

Installation Guidelines  
Maintenance Guidelines

FloorScore Certified


Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.


\*\*\*\*\*Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.


Available Colorways




Oyster Shell Oak 87140  
V3 - Moderate Variation




Antique Oak 87150  
V3 - Moderate Variation




Grain Wenge 87210  
V2 - Slight Variation




Barley Oak 87220  
V3 - Moderate Variation




Sesame Oak 87240  
V3 - Moderate Variation




Honey Wenge 87250  
V2 - Slight Variation




Palladium Oak 87515  
V3 - Moderate Variation




Liquorice Oak 87570  
V4 - Substantial Variation




Ginger Oak 87630  
V4 - Substantial Variation



Buckskin Oak 87660  
V3 - Moderate Variation



Nubuck Oak 87700  
V4 - Substantial Variation





Clove Walnut 87710  
V3 - Moderate Variation





 **Quick Ship** Immediately - In Stock Australia

**Color and Visual Variation Index**  
Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1  
  
Uniform Appearance

V2  
  
Slight Variation

V3  
  
Moderate Variation

V4  
  
Substantial Variation

