

Sentiment

Product Type	Broadloom	
Collection	Living Environments	
Style Number	60775	
Construction	Cut Pile	
Fiber	Nylon	
Primary Backing	Polypropylene	
Secondary Backing	Classicbac®	
Protective Treatments	R2x® Stain And Soil Resistance System	
Recommended Adhesive	H1000, H1200 or H3800	

	metric	U.S.
Product Size	3.66 m	12 ft
Gauge	31.5 per 10 cm	1/8 in
Stitches	43.5 per 10 cm	11.0 per in
Average Density	0.098 g/cm³	2647 oz/yd³
Kilotex	6.74	
Total Thickness	8.69 mm	0.342 in
Tufted Weight	847.6 g/m²	25 oz/yd²
Installation Pattern Repeat	2.54 cm x 2.54 cm	1 in x 1 in



Recommended Installation Method

Direct Glue, Double Glue, Stretch-In

Product should be installed in rooms only applications.

When installing in hybrid locations with carpet and resilient, direct glue with LokSeam is recommended.

Performance + Testing

Pill Test	Pass
CRI Green Label Plus (GLP)	GLP8878

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Material Health & Environmental Certifications

Cradle to Cradle Certified®
Environmental Product Declaration (EPD)
NSF 140
CRI Green Label Plus (GLP)
Environmental Guarantee*
Total Recycled Content
Product Packaging
Country of Origin**

Silver Level (Version 3.1)
3rd Party Certified in Accordance with ISO14044, ISO14025 & EN15804
Gold
GLP8878
Re[turn] Reclamation Program* Pickup & Delivery Available
<1% (Pre-Consumer <1% Post-Consumer 0%)
100% Recyclable
USA








Coordinating Products

Broadloom: **Upscale, Imagery**

Leed v4 Contribution Credits

MR Credit: Building Product Disclosure and Optimization Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO14044, ISO14025 & EN15804
MR Credit: Building Product Disclosure and Optimization Material Ingredients - Option 1: Material Ingredient Reporting	C2C Silver Level (Version 3.1)
MR Credit: Building Product Disclosure and Optimization Material Ingredients - Option 2: Material Ingredient Optimization	C2C Silver Level (Version 3.1)
EQ Credit: Low Emitting Materials Option 1: Product Category Calculations	Certified

Available Colorways

					
Peaceful 00102	Gentle 00103	Still 00510	Harmony 00512	Assured 00523	Likable 00539
					
Gracious 00541	Engaging 00544	Friendship 00703	Nostalgia 00713	Emotion 00753	

Additional Information

* To learn more about the recyclability of our products and our Environmental Guarantee, please visit shawcontract.com/sustainability .	
**Meets or exceeds all local and national regulations in country of manufacture. (Manufactured in an ISO 9001 & ISO 14001 certified facility or equivalent)	
Installation Guidelines	Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.
Maintenance Guidelines	This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
	Visit shawcontract.com/testing for more information.