

Sentiment

Type De Produit	Moquette EN Lé
Collection	Living Environments
Numéro Du Style	60775
Construction	Pile Coupée
Fibre	Nylon
Sous-couche Primaire	Polypropylène
Sous-couche Secondaire	Classicbac®
Traitements Protecteurs	Système De Résistance Aux Taches Et Aux Salissures R2x®
Adhésif Recommandé	H1000, H1200 or H3800

	u.s.	metric
Dimensions Du Produit	12 ft	3.66 m
Jauge	1/8 in	31.5 per 10 cm
Points	11.0 per in	43.5 per 10 cm
Densité Moyenne	2647 oz/yd³	0.098 g/cm³
Kilotex		6.74
Epaisseur Du Velours	0.342 in	8.69 mm
Poids Tufté	25 oz/yd²	847.6 g/m²
Installation Répétition Du Motif	1 in x 1 in	2.54 cm x 2.54 cm



Méthodes d'Installation Conseillées

Direct Glue, Double Glue, Stretch-In

Product should be installed in rooms only applications.

When installing in hybrid locations with carpet and resilient, direct glue with LokSeam is recommended.

Données + Tests Et Essai

Test d'Inflammabilité	Pass
Label Cri Green Label Plus (Glp)	GLP8878

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Attributs + Certifications

- Certification Cradle to Cradle™ (C2C)
- Déclaration environnementale de produit (EPD)
- NSF 140
- CRI Green Label Plus (GLP)
- Label CE (EN 14041)
- garantie environnementale
- contenu recyclé total
- emballage du produit
- pays d'origine

Silver Level (Version 3.1)
Certifié Par Un Organisme Tiers Conformément Aux Normes ISO 14044, ISO 14025 & EN15804
or
GLP8878
Certifié Par Un Organisme Tiers
Re[turn] Reclamation Program* | Pickup & Delivery Available
<1% (Pre-Consumer <1% | Post-Consumer 0%)
100% Recyclable
USA












Coordination Des Produits

Broadloom: Upscale, Imagery

Contribution À La Certification Leed

MR Credit: Building Product Disclosure and Optimisation Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO14044, ISO14025 & EN15804
MR Credit: Building Product Disclosure and Optimisation Material Ingredients - Option 1: Material Ingredient Reporting	C2C Silver Level (Version 3.1)
MR Credit: Building Product Disclosure and Optimisation Material Ingredients - Option 2: Material Ingredient Optimization	C2C Silver Level (Version 3.1)
"Crédit EQ : matériaux faibles émissions Option 1 : calculs par catégorie de produit"	Certified

Available Colorways

					
Peaceful 00102	Gentle 00103	Still 00510	Harmony 00512	Assured 00523	Likable 00539
					
Gracious 00541	Engaging 00544	Friendship 00703	Nostalgia 00713	Emotion 00753	

Informations Supplémentaires

* To learn more about the recyclability of our products and our Environmental Guarantee, please visit shawcontract.com/sustainability .	
**Meets or exceeds all local and national regulations in country of manufacture. (Manufactured in an ISO 9001 & ISO 14001 certified facility or equivalent)	
Installation Guidelines	Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.
Maintenance Guidelines	This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
	Visit shawcontract.com/testing for more information.