

R | Liberty GD (glue down) PRODUCT SPECIFICATIONS

STYLE NUMBER	VX330	
CONSTRUCTION	Heavy Commercial Luxury Vinyl Tile	
	US Units	Metric Units
WEAR LAYER THICKNESS	20 mil / 0.02 inches	0.508 mm
OVERALL THICKNESS	0.157 inches	4 mm
EDGE PROFILE	Squared Edge	
FINISH	ExoGuard+®	
INSTALLATION TYPE	Dry Back	
INSTALLATION	Glue Down	
RECOMMENDED ADHESIVE	2200 (4 gal), 4200 (4 gal), 4252 (4 gal) or S150 SPRAY ADHS	

Packaging

PLANK SIZE	12 inches W x 24 inches L	30.5 cm W x 61 cm L
PIECES /BOX	11	
AREA /BOX	22 sq ft	2 sq m
WEIGHT /BOX	31.68 lbs	14.4 kg

Performance Testing

STATIC LOAD / ASTM F970	Passes (Modified), *1000 lbs	
RESISTANCE TO CHEMICALS / ASTM F925	Passes	
RADIANT PANEL / ASTM E648	Passes, Class I	
SMOKE DENSITY / ASTM E662	Passes	
COEFFICIENT OF FRICTION (ASTM D2047, SLIP RESISTANCE)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes	

*Results are based on a laboratory test and used for comparative purposes. Real life load limit may vary.

Warranty

[15 Year Commercial Limited.](#)

[Commercial Limited Underbed Bond Warranty.](#)

Please visit patcraft.com for the most current warranty information.

Materials

RECYCLED CONTENT	Pre-consumer - 35%
-------------------------	--------------------

Third Party Certifications

FLOORSCORE®	Certified
--------------------	---------------------------

R | Liberty GD (glue down)

Available Colorways



CANVAS-V2 00110



OCHRE-V2 00140



GESSO-V2 00510



GRAPHITE-V2 00530



CHARCOAL-V2 00560



SUMI-V2 00580



UMBER-V2 00730



SEPIA-V2 00760