

R | **Extend** PRODUCT SPECIFICATIONS



STYLE NUMBER	VX226
CONSTRUCTION	Commercial Luxury Vinyl Plank
WEAR LAYER THICKNESS	20 mil / 0.02 inches (0.508 mm)
OVERALL THICKNESS	0.098 inches (2.5 mm)
FINISH	ExoGuard+®
INSTALLATION TYPE	Dry Back
INSTALLATION	Glue Down
RECOMMENDED ADHESIVE	200 (1 gal), 200 (4 gal), 2200 (1 gal), 2200 (4 gal), 4151, 4200 Resilient or S150 SPRAY ADHS

Packaging

PLANK SIZE
PIECES /BOX
AREA /BOX
WEIGHT /BOX

US Units
 7.75 inches W x 48 inches L
 21
 54.18 sq ft
 43.8 lbs

Metric Units
 19.7 cm W x 121.9 cm L
 5 sq m
 19.9 kg

Performance Testing

STATIC LOAD / ASTM F970	Passes (Modified), *1500 lbs
RESIDUAL INDENTATION / ASTM F1914	Passes
RESISTANCE TO CHEMICALS / ASTM F925	Passes
RADIANT PANEL / ASTM E648	Passes, Class I
SMOKE DENSITY / ASTM E662	Passes

*Results are based on a laboratory test and used for comparative purposes. Real life load limit may vary.

Warranty


15 Year Commercial Limited.

Commercial Limited Underbed Bond Warranty.


Please visit patcraft.com for the most current warranty information.

R | Extend

Installation Methods



Brick



Herringbone



Stagger

Materials

RECYCLED CONTENT

Pre-consumer - 30%

Third Party Certifications

FLOORSCORE®

Certified

Available Colorways

AMARETTO-V3 00740