



7295 Modern Classic

	US Units	Metric Units
Style Number	VE210	
Construction	SPC	
Profile	Click	
Size	7" x 48"	17.78 cm x 121.92 cm
Overall Thickness	0.189"	4.8 mm
Wear Layer Thickness	12 mil (0.012")	0.3 mm
Attached Underlayment	EVA Pad	
Attached Underlayment Thickness	0.059"	1.5 mm
Finish	ArmourBead®	
Edge Description	Micro Bevel	
Area per Carton	18.67 sq ft	1.73 sq m
Area per Pallet	1493.6 sq ft	138.76 sq m
Installation Methods	Floating	
Installation Grade	All Levels of the Home	
Environmental	FloorScore® Certified	
Residential Warranty	30 Year Residential Resilient Limited Warranty	
Commercial Warranty	Resilient SPC 7 Year Commercial Limited Warranty	
Installation	Luxury Vinyl Angle/Angle SPC	
Maintenance	Residential Resilient Maintenance	
Radiant Panel (ASTM E648)	Passes, Class I	

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Features

Rich hues, combined with beveled edges and realistic embossing embody the tried-and-true character of real hardwood. Optimum is 100% waterproof for a beautiful, high-performing floor and features Soft Silence® acoustical pad for noise reduction and added comfort.

Colors



150 Cinnamon Walnut



154 Almond Oak



203 Tawny Oak



556 Smoky Oak



591 Oyster Oak



Suggested Adhesive




Style Name	Style Number
Shaw T-180 (4 gal)	

Coordinating Trim

Baby Threshold*	T-Molding*	Multi-Purpose Reducer	Quarter Round	Overlap Stairnose	Flush Stairnose
BT3HB 94"	HSTMD 94" TM3HB 94"	RD3HB 94"	QTRHB 94"	HSSTN 94" HSST6 94"	FS4HB 94" HFSN2 94"

*Packaged with molding track

Coordinating Metal Trim



Finish	Reducer	T-Mold	Stair Cap
Satin Silver	190BA	193BA	187BA
Satin Nickel	191BA	194BA	188BA

Installation Range

Profile Size	Installation Range
3.5mm	1.5mm to 3.5mm heights
5.5mm	3.6mm to 5.5mm heights
8mm	6mm to 8mm heights