

|                           | US Units  | Metric Units           |
|---------------------------|---|------------------------|
| Style Number              | VG069   |                        |
| Construction              | Residential Resilient - Sheet                                 |                        |
| Profile                   | Direct Glue   |                        |
| Size                      | 144" x 1572"  | 365.76 cm x 3992.88 cm |
| Overall Thickness         | 0.065"  | 1.654 mm               |
| Wear Layer Thickness      | 10 mil (0.01")  | 0.3 mm                 |
| Finish                    | Opticlean Urethane  |                        |
| Installation Methods      | Direct Glue   |                        |
| Installation Grade        | All Levels of the Home  |                        |
| Environmental             | FloorScore® Certified   |                        |
| Residential Warranty      | 10 Years  |                        |
| Installation              | <a href="#">Duratru Resilient Flooring Installation Guide</a> |                        |
| Radiant Panel (ASTM E648) | Passes, Class I   |                        |

Features

This style features the wide width sturdy boards that helped the Pioneers settle in the mid-west. The stunning wood designs are depicted in large format robust sheet vinyl just the actual boards themselves. Colors that match the rustic/weathered look of the plains.

Suggested Adhesive

| Style Name         | Style Number       |
|--------------------|--------------------|
| SHAW 350 PS ADH 4G | 024VS              |
| 124VS              | VS053              |
| 053VS              | SHAW SV-1200 1 GAL |
| VS186              | 100BA              |
| SHAW SV-1200 4 GAL | 101SA              |
| 101BA              |                    |



**TREADZ®**

Center

Right

Left

White Riser \*

\*packages of 3

