


Fragment Comfortworx® Tile

| | | |
|---------------------------|------------------------|---|
| Número Du Style | C019W | |
| Collection | Floor Architecture III | |
| Type De Produit | Dalles De Moquette | |
| Construction | Standard | Data + Performance |
| Type De Fabrication | ISO 2424 | tufted 1/12" 47.2 per 10cm |
| Construction | ISO 2424 | Tufté Structuré Bouclé à Motif |
| Méthode De Coloration | EN 994 | 100% Solution Teinte |
| Dimensions Du Produit | EN 994 | 50 cm x 50 cm 16 tiles (4 m²) per box |
| Sous-couche Primaire | ISO 2424 | Pet Non-Woven |
| Sous-couche Secondaire | ISO 2424 | Comfortworx® Tile La Couche Matrix Pad Contient 90 % De Contenu Recyclé |
| Fibre | ISO 2424 | Ecosolution Q® Polyamide 6 |
| Epaisseur Du Velours | ISO 1765 | 11.3 mm |
| Épaisseur Du Velours Fini | ISO 1766 | 2.9 mm |
| Poids Total | ISO 8543 | 4262 g/m² |
| Poids Tufté | ISO 2424 | 630 g/m² |
| Poids Du Velours Utile | ISO 8543 | 288 g/m² |
| Densité Du Velours | ISO 8543 | 0.097 g/cm³ |
| Données | | |


| | | |
|---------------------------------------|---------------|----------------------------|
| Points | ISO 1763 | 193,000/m² 41.0 per 10cm |
| Propension Electrostatique | ISO 6356 | ≤ 2.0 kv (Stroll Test) |
| Classification d'Utilisation | EN 1307 | 33 Commercial Heavy |
| Classification Luxe | EN 1307 | LC1 |
| Stabilité Dimensionnelle | EN 986 | ≤ 0.2% |
| Isolation Acoustique | ISO 10140 | 37db |
| Classification d'Absorption Sonore | ISO 354/11654 | 0.30 Aw Class D |
| Résistance Thermique m² K/w | ISO 8302 | 0.162 M² K/W Tog 1.62 |
| Dry Slip Resistance | ISO 13893 | Pass / No Pulled Loops |
| Résistance De La Couleur À La Lumière | ISO 105-B02 | >6 |
| Inflammabilité | EN 13501-1 | Bfl-S1 (Adhered Testing) |
| Chaise À Roulette | EN 985 | ≥2.4 Continuous USE |

Limitée Commerciale De 15 Ans subject to installation in full accordance with manufacturer's instructions and a regular effective cleaning and maintenance programme.


Méthodes d'Installation Conseillées




Monolithic




Quarter Turn








Brick






Ashlar




Random






37dB







20

EU.DOP/2895/CPR/0820/1020/BT
OOSTERHOUT SHOWROOM, VAARTWEG 10, 4905
BL NETHERLANDS (NLD)
Notified Body 2895



22

UK.DOP/0338/CPR/0820/1020/BT
SHAW EUROPE LIMITED BLACKADDIE RD,
SANQUHAR DG4 6DB, UNITED KINGDOM
Approved Body 0338



EN14041:2004/AC:2006

For use as an indoor floor covering as specified by the manufacturer

Coordination Des Produits

Carpet Tile: **Stone Comfortworx® Tile, Formation Colours Comfortworx® Tile, Fragment Colours Comfortworx® Tile, Stone Colours Comfortworx® Tile, Formation Comfortworx® Tile, Fragment Taskworx® Tile, Stone Taskworx® Tile, Formation Colours Ecoworx S Tile, Fragment Colours Ecoworx S Tile, Formation Colours Taskworx® Tile, Fragment Colours Taskworx® Tile, Fragment Ecoworx S Tile, Stone Ecoworx S Tile, Formation Taskworx® Tile, Formation Ecoworx S Tile, Stone Colours Taskworx® Tile, Stone Colours Ecoworx® S Tile**

Attributs + Certifications

| | |
|---|---|
| Declaration of Performance | EU.DOP/2895/CPR/0820/1020/BT |
| Déclaration environnementale de produit (EPD) | Certifié Par Un Organisme Tiers Conformément Aux Normes ISO14044, ISO 14025 & EN15804 |
| garantie environnementale | Take Back Policy Offered For All Comfortworx Products |
| ISO 9001 | Certifié |
| pays d'origine | United Kingdom |
| BREEAM Contribution Credit | Certificate of Approval Schools/Offices/Health/Industrial Shed Retail |

Well V2 Contribution Credit

| | |
|--|---|
| X11 Long Term Emissions Control Part 2: Flooring Optimization | M1> Emissions Class For Building Material |
|--|---|

Contribution À La Certification Leed

| | |
|---|---|
| MR Credit: Building Product Disclosure and Optimisation Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD) | 3rd Party Certified in Accordance with ISO14044, ISO14025 & EN15804 |
| MR Credit: Building Product Disclosure and Optimisation Material Ingredients - Option 1: Material Ingredient Reporting | HPD (Version 2.1) |
| "Crédit EQ : matériaux faibles émissions Option 1 : calculs par catégorie de produit" | Certified |










Air Quality

| | |
|-------------------------|-----------|
| Indoor Air Comfort Gold | Certified |
| M1 | Certified |

Memberships

| | |
|---------------------------------|---------------------------------|
| WGBC Framework | WGBC Framework |
| UKGBC | UKGBC |
| Emirates Green Building Council | Emirates Green Building Council |
| Chemsec | Chemsec |

Indice De Réflexion Lumineuse

| | | | | | |
|--|---|---|--|---|---|
|  |  |  |  |  |  |
| Marble 53100 LRV 25.9 L* 57.97 | Azurite 53485 LRV 3.1 L* 20.53 | Granite 53500 LRV 3.3 L* 21.3 | Mica 53518 LRV 10.2 L* 38.26 | Mortar 53530 LRV 11.5 L* 40.44 | Limestone 53535 LRV 13.2 L* 43.01 |
|  |  |  | | | |
| Anthracite 53555 LRV 5.8 L* 29.94 | Chromite 53580 LRV 10.3 L* 38.38 | Mix 53597 LRV 7 L* 31.88 | | | |

Informations Supplémentaires

**Manufactured in ISO 9001 certified facility. Meets or exceeds all local and national regulations in country of manufacture.

[Installation Guidelines](#)

Limitée commerciale de 15 ans

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

