

## Roam Comfortworx® Tile

Stijlnummer	<b>C001W</b>	
Collectie	<b>Rapid Select</b>	
Producttype	<b>Tapijttegels</b>	
Construction	Standard	Data + Performance
Type Fabricage	<b>ISO 2424</b>	<b>tufted 1/12"   47.2 per 10cm</b>
Uitzicht	<b>ISO 2424</b>	<b>Multilevel-Patroonlus</b>
Verfmethode	<b>EN 994</b>	<b>100% In Oplossing Geveerd</b>
Productformaat	<b>EN 994</b>	<b>25 cm x 100 cm   16 tiles (4 m²) per box</b>
Primaire Backing	<b>ISO 2424</b>	<b>Pet Nonwoven</b>
Secundaire Backing	<b>ISO 2424</b>	<b>Comfortworx® Tegels   Matrix Padlaag Bevat 90% Gerecycleerd Materiaal</b>
Vezel	<b>ISO 2424</b>	<b>Ecosolution Q® Polyamide 6</b>
Totale Dikte	<b>ISO 1765</b>	<b>10.8 mm</b>
Afgewerkte Pooldikte	<b>ISO 1766</b>	<b>2.7 mm</b>
Totale Massa	<b>ISO 8543</b>	<b>4195 g/m²</b>
Getuft Gewicht	<b>ISO 2424</b>	<b>616 g/m²</b>
Effectieve Poolmassa	<b>ISO 8543</b>	<b>313 g/m²</b>
Pool dichtheid	<b>ISO 8543</b>	<b>0.113 g/cm³</b>
Totaal Gerecycleerde Inhoud		<b>57% (pre-consumer 45%   post-consumer 12%)</b>




### Gegevens

Steken	<b>ISO 1763</b>	<b>217,000/m²   45.9 per 10cm</b>
Elektrostatische Weerstand	<b>ISO 6356</b>	<b>≤ 2.0 kv (Stroll Test)</b>
Gebruik Classificatie	<b>EN 1307</b>	<b>33 Commercial Heavy</b>
Luxe klasse	<b>EN 1307</b>	<b>LC1</b>
Dimensionale Stabiliteit	<b>EN 986</b>	<b>≤ 0.2%</b>
Contactgeluidsisolatie	<b>ISO 10140</b>	<b>37db</b>
Geluidsabsorptieclassificatie	<b>ISO 354/11654</b>	<b>0.30 Aw   Class D</b>
Warmteweerstand m² K/w	<b>ISO 8302</b>	<b>0.168 M² K/W Tog 1.68</b>
Weerstand Tegen Droog Uitglijden	<b>ISO 13893</b>	<b>Pass / No Pulled Loops</b>
Kleurvastheid Voor Licht	<b>ISO 105-B02</b>	<b>&gt;6</b>
Ontvlambaarheid	<b>EN 13501-1</b>	<b>Bfl-S1 (Adhered Testing)</b>
Stoel Met Wielletjes	<b>EN 985</b>	<b>≥2.4 Continuous Use</b>

**15 Jaar Commercieel Beperkt** subject to installation in full accordance with the manufacturer's instructions and a regular effective cleaning and maintenance programme. Second location warranties are available with the use of non-adhesive IOBAC Magtabs and Tabit accessories.

### Aanbevolen Installatiemethode



<b>CE</b> 20 EU.DOP/2895/CPR/0820/1020/BT OOSTERHOUT SHOWROOM, VAARTWEG 10, 4905 BL NETHERLANDS (NLD) Notified Body 2895	<b>UK</b> CA 22 UK.DOP/0338/CPR/0820/1020/BT SHAW EUROPE LIMITED BLACKADDIE RD, SANQUHAR DG4 6DB, UNITED KINGDOM Approved Body 0338
<b>E1</b> HCHO	<b>Bfl-s1</b>
<b>EN14041:2004/AC:2006</b> For use as an indoor floor covering as specified by the manufacturer	<b>DS</b>

## Coördinerende Producten

Carpet Tile: **Graph Comfortworx® Tile, Nook Comfortworx® Tile, Graph Taskworx® Tile, Roam Taskworx® Tile, Nook Taskworx® Tile**

## Kenmerken + Certificeringen

Declaration of Performance

**EU.DOP/2895/CPR/0820/1020/BT**

Environmental Product Declaration (EPD)

**3de Partij Gecertificeerd in Overeenstemming Met ISO14044, ISO14025 & EN15804**

milieugarantie

**Take Back Policy Offered For All Comfortworx Products**

ISO 9001

**Gecertificeerd**

land van herkomst

**Verenigd Koninkrijk**

BREEAM Contribution Credit

**Certificate of Approval  
Schools/Offices/Health/Industrial Shed  
Retail**

## Well V2 Contribution Credit

X11 Langetermijn-emissiebeheersing - deel 2: Optimalisering van vloeren - 1 pt **M1> Emissions Class For Building Material**

## Groen Leed Bijdragekrediet

"MR-krediet: openbaarmaking en optimalisering van bouwproducten  
Milieuproductverklaringen - Optie 1: Milieuproductverklaring (EPD)"

**3rd Party Certified in Accordance with ISO14044, ISO14025 & EN15804**

"MR-krediet: Openbaarmaking en optimalisering van bouwproducten  
Materiaalingrediënten - Optie 1: Rapportage materiaalingrediënten"

**HPD ( Version 2.1 )**

## Air Quality

Indoor Air Comfort Gold

**Certified**

M1

**Certified**

## Memberships

WGBC Framework

**WGBC Framework**

UKGBC

**UKGBC**



Emirates Green Building Council

**Emirates Green Building Council**

Chemsec

**Chemsec**

## Lichtreflectiewaarde

					
Cotswold 26100 LRV 25.9   L* 57.91	Grey Mist 26481 LRV 11.3   L* 40.07	Flint 26505 LRV 2.9   L* 19.82	Cobblestone 26515 LRV 15.3   L* 46.06	Mountain 26518	Sussex Grey 26535 LRV 10.1   L* 38
					
Shadow 26557 LRV 5.7   L* 28.7	Stone Gate 26760 LRV 10.1   L* 37.97				

## Aanvullende Informatie

\*\*Manufactured in ISO 9001 certified facility. Meets or exceeds all local and national regulations in country of manufacture.

[Installation Guidelines](#)

[15 jaar commercieel beperkt](#)

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](https://shawcontract.com/testing) for more information.



Corporate Headquarters +1 800 257 7429 | +1 706 532 7984 | Atlanta +1 404 853 7429 | Bengaluru +91 80 6773 0202 | Beijing +86 10 6568 588 | Chicago +1 312 467 1331 | Dubai +971 4 584 6956 | Hong Kong +852 2623 0371 | London +44 207 961 4120 | Los Angeles +1 800 233 1614 | Melbourne +61 3 9939 8543 | Mexico City +55 5010 7600 | Mumbai +91 22 6284 5050 | Nantong +86 400 800 7429 | New York +1 212 953 7429 | Paris +33 (0) 1 81 22 44 39 | San Francisco +1 415 955 1920 | Shanghai +86 21 3338 4000 | Singapore +65 6733 1811 | Sydney +61 800 556 302

© 2025 Shaw Industries Group, Inc., a Berkshire Hathaway Company  
June 7, 2025

3 of 3