

## Pixel Rectangle Comfortworx® Tile

Style Number	<b>C004W</b>	
Collection	<b>Colour Construct</b>	
Product Type	<b>Carpet Tile</b>	
Construction	Standard	Data + Performance
Type of Manufacture	<b>ISO 2424</b>	<b>tufted 1/12"   47.2 per 10cm</b>
Aspect	<b>ISO 2424</b>	<b>Multi-Level Pattern Loop</b>
Dye Method	<b>EN 994</b>	<b>100% Solution Dyed</b>
Dimensions	<b>EN 994</b>	<b>25 cm x 100 cm   16 tiles (4 m²) per box</b>
Primary Backing	<b>ISO 2424</b>	<b>Pet Non-Woven</b>
Secondary Backing	<b>ISO 2424</b>	<b>Comfortworx® Tile   Matrix Pad Layer Contains 90% Recycled Content</b>
Pile Fibre Composition	<b>ISO 2424</b>	<b>Eco Solution Q® Polyamide 6</b>
Total Thickness	<b>ISO 1765</b>	<b>10.8 mm</b>
Effective Pile Thickness	<b>ISO 1766</b>	<b>2.9 mm</b>
Total Mass	<b>ISO 8543</b>	<b>5652 g/m²</b>
Nominal Total Pile Mass	<b>ISO 2424</b>	<b>794 g/m²</b>
Effective Pile Mass	<b>ISO 8543</b>	<b>418 g/m²</b>
Pile Density	<b>ISO 8543</b>	<b>0.143 g/cm³</b>



### Performance

Number of Tufts	<b>ISO 1763</b>	<b>155,000/m²   32.8 per 10cm</b>
Electrostatic Propensity	<b>ISO 6356</b>	<b>≤ 2.0 kv (Stroll Test)</b>
Use Classification	<b>EN 1307</b>	<b>33 Commercial Heavy</b>
Luxury Class	<b>EN 1307</b>	<b>LC2</b>
Dimensional Stability	<b>EN 986</b>	<b>≤ 0.2%</b>
Impact Sound Insulation	<b>ISO 10140</b>	<b>35db</b>
Sound Absorption Classification	<b>ISO 354/11654</b>	<b>0.30 Aw   Class D</b>
Thermal Resistance m² K/W	<b>ISO 8302</b>	<b>0.154 M² K/W Tog 1.54</b>
Dry Slip Resistance	<b>ISO 13893</b>	<b>Pass / No Pulled Loops</b>
Colour Fastness To Light	<b>ISO 105-B02</b>	<b>&gt;6</b>
Flammability	<b>EN 13501-1</b>	<b>Bfl-S1 (Adhered Testing)</b>
Castor Chair	<b>EN 985</b>	<b>≥2.4 Continuous Use</b>

**15 Year Commercial Limited Warranty** subject to installation in full accordance with the manufacturer's instructions and a regular effective cleaning and maintenance programme. Second location warranties are available with the use of non-adhesive IOBAC Magtabs and Tabit accessories.

### Recommended Installation Method



Ashlar



Brick



Herringbone



Stagger



35dB



20

EU.DOP/2895/CPR/0820/1020/BT  
OOSTERHOUT SHOWROOM, VAARTWEG 10, 4905  
BL NETHERLANDS (NLD)  
Notified Body 2895



22

UK.DOP/0338/CPR/0820/1020/BT  
SHAW EUROPE LIMITED BLACKADDIE RD,  
SANQUHAR DG4 6DB, UNITED KINGDOM  
Approved Body 0338



EN14041:2004/AC:2006

For use as an indoor floor covering as specified by the manufacturer

Coordinating Products

Carpet Tile: **Pixel Square Comfortworx® Tile, Pixel Hexagon Taskworx® Tile, Pixel Square Taskworx® Tile, Pixel Rectangle Taskworx® Tile**

Product Transparency

Shaw Contract is dedicated to providing clients with a building chemistry that's safe and dependable. Working together, we will help you meet your goals as they pertain to material health. ComfortWorx® products are Cradle to Cradle Certified® Bronze and assessed for impacts on human health and the environment. This product can be recycled. When it's time to replace, we can collect through our re-[TURN] scheme in EMEA.

Material Health & Environmental Certifications

Declaration of Performance	<b>EU.DOP/2895/CPR/0820/1020/BT</b>
Environmental Product Declaration (EPD)	<b>3rd Party Certified in Accordance with ISO14044, ISO14025 &amp; EN15804</b>
Environmental Guarantee*	<b>Take Back Policy Offered For All Comfortworx Products</b>
ISO 9001	<b>Certified</b>
Country of Origin**	<b>United Kingdom</b>
BREEAM Contribution Credit	<b>Certificate of Approval Schools/Offices/Health/Industrial Shed Retail</b>

WELL V2 Contribution Credit

X11 Long Term Emissions Control Part 2: Flooring Optimization	<b>M1&gt; Emissions Class For Building Material</b>
--	---

Leed v4 Contribution Credits

MR Credit: Building Product Disclosure and Optimization Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)	<b>3rd Party Certified in Accordance with ISO14044, ISO14025 &amp; EN15804</b>
MR Credit: Building Product Disclosure and Optimization Material Ingredients - Option 1: Material Ingredient Reporting	<b>HPD ( Version 2.1 )</b>
EQ Credit: Low Emitting Materials Option 1: Product Category Calculations	<b>Certified</b>

Air Quality












Indoor Air Comfort Gold	<b>Certified</b>
M1	<b>Certified</b>

Memberships

WGBC Framework	<b>WGBC Framework</b>
UKGBC	<b>UKGBC</b>
Emirates Green Building Council	<b>Emirates Green Building Council</b>
Chemsec	<b>Chemsec</b>



Light Reflectance Value

 <div>Yellow 53211 LRV 26.5   L* 58.51</div>	 <div>Chartreuse 53326 LRV 17.3   L* 48.7</div>	 <div>Seaglass 53375 LRV 8.2   L* 34.34</div>	 <div>Aqua 53418 LRV 13.9   L* 44.07</div>	 <div>Wave 53432 LRV 6.8   L* 31.29</div>	 <div>Navy 53485 LRV 5.3   L* 27.47</div>
 <div>Blue 53486 LRV 9.5   L* 36.87</div>	 <div>Arctic 53501 LRV 31   L* 62.47</div>	 <div>Black 53505 LRV 2.6   L* 18.29</div>	 <div>Light Taupe 53506 LRV 16.8   L* 47.96</div>	 <div>Grey 53515 LRV 18.4   L* 49.99</div>	 <div>Beige 53516 LRV 23.4   L* 55.47</div>
 <div>Pewter 53518 LRV 11.3   L* 40.02</div>	 <div>Nickel 53535 LRV 18.9   L* 50.55</div>	 <div>Graphite 53549 LRV 3.9   L* 23.49</div>	 <div>Charcoal 53557 LRV 6.2   L* 29.85</div>	 <div>Steel 53580 LRV 7.5   L* 32.99</div>	 <div>Urban 53592 LRV 11.8   L* 40.83</div>
 <div>Gunmetal 53597 LRV 4.1   L* 23.93</div>	 <div>Orange 53668 LRV 12.8   L* 42.51</div>	 <div>Tangerine 53675 LRV 23.1   L* 55.22</div>	 <div>Taupe 53761 LRV 12.5   L* 42.06</div>	 <div>Poppy 53856 LRV 9.8   L* 37.45</div>	 <div>Magenta 53991 LRV 5.6   L* 28.35</div>

Additional Information

\*\*Manufactured in ISO 9001 certified facility. Meets or exceeds all local and national regulations in country of manufacture.

[Installation Guidelines](#)

[15 Year Commercial Limited warranty](#)

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

