

Landing Edge Comfortworx® Tile

| | | |
|----------------------|-----------------|--|
| Stijlnummer | C033W | |
| Collectie | Shifting Fields | |
| Producttype | Tapijttegel | |
| Construction | Standard | Data + Performance |
| Type Fabricage | ISO 2424 | tufted 1/10" 39.4 per 10cm |
| Uitzicht | ISO 2424 | Multilevel-Patroonlus |
| Verfmethode | EN 994 | 100% In Oplossing Geverfd |
| Productformaat | EN 994 | 50 cm x 50 cm 12 tiles (3 m²) per box |
| Primaire Backing | ISO 2424 | Pet Nonwoven |
| Secundaire Backing | ISO 2424 | Comfortworx® Tegel Matrix Padlaag Bevat 90% Gerecycleerd Materiaal |
| Vezel | ISO 2424 | Ecosolution Q100™ Polyamide 6 Bevat 100% Gerecycleerd Materiaal |
| Totale Dikte | ISO 1765 | 11.8 mm |
| Afgewerkte Pooldikte | ISO 1766 | 2.4 mm |
| Totale Massa | ISO 8543 | 5157 g/m² |
| Getuft Gewicht | ISO 2424 | 746 g/m² |
| Effectieve Poolmassa | ISO 8543 | 286 g/m² |
| Pooldichtheid | ISO 8543 | 0.119 g/cm³ |



Gegevens

| | | |
|----------------------------------|---------------|-----------------------------|
| Steken | ISO 1763 | 120,000/m² 30.5 per 10 cm |
| Elektrostatische Weerstand | ISO 6356 | ≤ 2.0 kv (Stroll Test) |
| Gebruik Classificatie | EN 1307 | 33 Commercial Heavy |
| Luxeklasse | EN 1307 | LC1 |
| Dimensionale Stabiliteit | EN 986 | ≤ 0.2% |
| Contactgeluidsisolatie | ISO 10140 | 35db* |
| Geluidsabsorptieclassificatie | ISO 354/11654 | 0.30 Aw Class D |
| Warmteweerstand m² K/w | ISO 8302 | 0.165 M² K/W Tog 1.65 |
| Weerstand Tegen Droog Uitglijden | ISO 13893 | Pass / No Pulled Loops |
| Kleurvastheid Voor Licht | ISO 105-B02 | >6 |
| Ontvlambaarheid | EN 13501-1 | Bfl-S1 (Adhered Testing) |
| Stoel Met Wieltjes | EN 985 | ≥2.4 Continuous USE |

15 Jaar Commercieel Beperkt subject to installation in full accordance with manufacturer's instructions and a regular effective cleaning and maintenance programme.

Aanbevolen Installatiemethode

Monolithic

Quarter Turn

Random

35dB

Coördinerende Producten

Carpet Tile: **Landing Comfortworx® Tile, Plains Comfortworx® Tile, Landing Edge Taskworx® Tile, Landing Taskworx® Tile, Plains Taskworx® Tile**

Kenmerken + Certificeringen

| | |
|----------------------------------|---|
| Embodied Carbon (Cradle to Gate) | 4.78 kg CO ₂ /m ² |
| Life-Cycle Carbon Emissions | Carbon Neutral |
| land van herkomst | Verenigd Koninkrijk |
| BREEAM Contribution Credit | Certificate of Approval Schools/Offices/Health/Industrial Shed Retail |







Air Quality

| | |
|-------------------------|-----------|
| Indoor Air Comfort Gold | Certified |
| M1 | Certified |

Memberships

| | |
|---------------------------------|---------------------------------|
| WGBC Framework | WGBC Framework |
| UKGBC | UKGBC |
| Emirates Green Building Council | Emirates Green Building Council |
| Chemsec | Chemsec |

Available Colorways



Remote Coast 71323Desert Tide 71327Pristine Evergr 71334Remote Reservoir 71485Pristine Stone 71595Desert Sunset 71675

E8031 E8031

Aanvullende Informatie

| | |
|-----------------------------|---|
| 15 jaar commercieel beperkt | Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice. This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited. Visit shawcontract.com/testing for more information. |
|-----------------------------|---|

