



Plains Comfortworx® Tile


Stijlnummer	C034W	
Collectie	Shifting Fields	
Producttype	Tapijttegel	
Construction	Standard	Data + Performance
Type Fabricage	ISO 2424	tufted 1/10" 39.4 per 10cm
Uitzicht	ISO 2424	Multilevel-Patroonlus
Verfmethode	EN 994	100% In Oplossing Geverfd
Productformaat	EN 994	50 cm x 50 cm 12 tiles (3 m²) per box
Primaire Backing	ISO 2424	Pet Nonwoven
Secundaire Backing	ISO 2424	Comfortworx® Tegel Matrix Padlaag Bevat 90% Gerecycleerd Materiaal
Totale Dikte	ISO 1765	11.9 mm
Afgewerkte Pooldikte	ISO 1766	2.3 mm
Totale Massa	ISO 8543	4659 g/m²
Getuft Gewicht	ISO 2424	746 g/m²
Effectieve Poolmassa	ISO 8543	271 g/m²
Pooldichtheid	ISO 8543	0.114 g/cm³
Totaal Gerecycleerde Inhoud		70% (pre-consumer 59% post-consumer 11%)

Gegevens


Steken	ISO 1763	116,000/m² 29.5 per 10 cm
Elektrostatische Weerstand	ISO 6356	≤ 2.0 kv (Stroll Test)
Gebruik Classificatie	EN 1307	33 Commercial Heavy
Luxeklasse	EN 1307	LC1
Dimensionale Stabiliteit	EN 986	≤ 0.2%
Contactgeluidsisolatie	ISO 10140	35db*
Geluidsabsorptieclassificatie	ISO 354/11654	0.30 Aw Class D
Warmteweerstand m² K/w	ISO 8302	0.165 M² K/W Tog 1.65
Weerstand Tegen Droog Uitglijden	ISO 13893	Pass / No Pulled Loops
Kleurvastheid Voor Licht	ISO 105-B02	>6
Ontvlambaarheid	EN 13501-1	Bfl-S1 (Adhered Testing)
Stoel Met Wieltjes	EN 985	≥2.4 Continuous USE

15 Jaar Commercieel Beperkt subject to installation in full accordance with the manufacturer's instructions and a regular effective cleaning and maintenance programme. Second location warranties are available with the use of non-adhesive IOBAC Magtabs and Tabit accessories.


Aanbevolen Installatiemethode




Monolithic




Quarter Turn



Brick



Ashlar



Random





35dB

Coördinerende Producten

Carpet Tile: **Landing Comfortworx® Tile, Landing Edge Comfortworx® Tile, Landing Edge Taskworx® Tile, Landing Taskworx® Tile, Plains Taskworx® Tile**

Kenmerken + Certificeringen

Embodied Carbon (Cradle to Gate)	4.78 kg CO ₂ /m ²
Life-Cycle Carbon Emissions	Carbon Neutral
land van herkomst	Verenigd Koninkrijk
BREEAM Contribution Credit	Certificate of Approval Schools/Offices/Health/Industrial Shed Retail


Air Quality

Indoor Air Comfort Gold	Certified
M1	Certified


Memberships

WGBC Framework	WGBC Framework
UKGBC	UKGBC
Emirates Green Building Council	Emirates Green Building Council
Chemsec	Chemsec


Available Colorways




Desert 71106




Coast 71323




Tide 71327




Evergreen 71334




Reservoir 71485




Pristine 71535




Remote 71580



Stone 71595



Sunset 71675



F1172 F1172

Aanvullende Informatie

15 jaar commercieel beperkt	Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice. This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited. Visit shawcontract.com/testing for more information.
-----------------------------	---

