

Stone Colours Comfortworx® Tile

Style Number	C040W	
Collection	Floor Architecture III	
Product Type	Carpet Tile	
Construction	Standard	Data + Performance
Type of Manufacture	ISO 2424	tufted 1/10"   39.4 per 10cm
Aspect	ISO 2424	Multi-Level Pattern Loop
Dye Method	EN 994	100% Solution Dyed
Dimensions	EN 994	50 cm x 50 cm   16 tiles (4 m²) per box
Primary Backing	ISO 2424	Pet Non-Woven
Secondary Backing	ISO 2424	Comfortworx® Tile   Matrix Pad Layer Contains 90% Recycled Content
Pile Fibre Composition	ISO 2424	Eco Solution Q® Polyamide 6
Total Thickness	ISO 1765	11.1 mm
Effective Pile Thickness	ISO 1766	2.8 mm
Total Mass	ISO 8543	4069 g/m²
Nominal Total Pile Mass	ISO 2424	630 g/m²
Effective Pile Mass	ISO 8543	308 g/m²
Pile Density	ISO 8543	0.109 g/cm³
Performance		
Number of Tufts	ISO 1763	165,000/m²   42 per 10cm
Electrostatic Propensity	ISO 6356	≤ 2.0 kv (Stroll Test)
Use Classification	EN 1307	33 Commercial Heavy
Luxury Class	EN 1307	LC1
Dimensional Stability	EN 986	≤ 0.2%
Impact Sound Insulation	ISO 10140	37db
Sound Absorption Classification	ISO 354/11654	0.30 Aw   Class D
Thermal Resistance m² K/W	ISO 8302	0.179 M² K/W Tog 1.79
Dry Slip Resistance	ISO 13893	Pass / No Pulled Loops
Colour Fastness To Light	ISO 105-B02	>6
Flammability	EN 13501-1	Bfl-S1 (Adhered Testing)
Castor Chair	EN 985	≥2.4 Continuous USe
15 Year Commercial Limited Warranty subject to installation in full accordance with manufacturer's instructions and a regular effective cleaning and maintenance programme.		

Recommended Installation Method

Monolithic

Quarter Turn

Brick

Ashlar

Random

37dB

Coordinating Products

Carpet Tile: **Stone Comfortworx® Tile, Fragment Comfortworx® Tile, Formation Colours Comfortworx® Tile, Fragment Colours Comfortworx® Tile, Formation Comfortworx® Tile, Fragment Taskworx® Tile, Stone Taskworx® Tile, Formation Colours Ecoworx S Tile, Fragment Colours Ecoworx S Tile, Formation Colours Taskworx® Tile, Fragment Colours Taskworx® Tile, Fragment Ecoworx S Tile, Stone Ecoworx S Tile, Formation Taskworx® Tile, Formation Ecoworx S Tile, Stone Colours Taskworx® Tile, Stone Colours Ecoworx® S Tile**

Product Transparency

Shaw Contract is dedicated to providing clients with a building chemistry that's safe and dependable. Working together, we will help you meet your goals as they pertain to material health. ComfortWorx® products are Cradle to Cradle Certified® Bronze and assessed for impacts on human health and the environment. This product can be recycled. When it's time to replace, we can collect through our re-[TURN] scheme in EMEA.

Material Health & Environmental Certifications

Environmental Product Declaration (EPD)	<b>3rd Party Certified in Accordance with ISO14044, ISO14025 &amp; EN15804</b>
Environmental Guarantee*	<b>Take Back Policy Offered For All Comfortworx Products</b>
ISO 9001	<b>Certified</b>
Country of Origin**	<b>United Kingdom</b>
BREEAM Contribution Credit	<b>Certificate of Approval Schools/Offices/Health/Industrial Shed Retail</b>

WELL V2 Contribution Credit

X11 Long Term Emissions Control Part 2: Flooring Optimization	<b>M1&gt; Emissions Class For Building Material</b>
------------------------------------------------------------------	-----------------------------------------------------



















Leed v4 Contribution Credits

MR Credit: Building Product Disclosure and Optimization Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)	<b>3rd Party Certified in Accordance with ISO14044, ISO14025 &amp; EN15804</b>
MR Credit: Building Product Disclosure and Optimization Material Ingredients - Option 1: Material Ingredient Reporting	<b>HPD ( Version 2.1 )</b>

Memberships

WGBC Framework	<b>WGBC Framework</b>
UKGBC	<b>UKGBC</b>
Emirates Green Building Council	<b>Emirates Green Building Council</b>
Chemsec	<b>Chemsec</b>

Light Reflectance Value

 <div>Oatmeal 04111 LRV 31.9   L* 63.25</div>	 <div>Brushed Gold 04210 LRV 24.6   L* 56.69</div>	 <div>Midnight Brushed 04211 LRV 8.1   L* 34.2</div>	 <div>Mineral 04327 LRV 22.9   L* 54.94</div>	 <div>Midnight Mineral 04328 LRV 12.5   L* 42.02</div>	 <div>Racing Green 04334 LRV 6.2   L* 29.9</div>
 <div>Sage 04375 LRV 22.3   L* 54.39</div>	 <div>Midnight Sage 04376 LRV 7.5   L* 32.97</div>	 <div>Sky 04411 LRV 24.9   L* 56.96</div>	 <div>Midnight Sky 04412 LRV 9.6   L* 37.08</div>	 <div>Steel Blue 04447</div>	 <div>Denim 04486 LRV 10   L* 37.8</div>
 <div>Midnight Apricot 04674 LRV 7.8   L* 33.46</div>	 <div>Apricot 04675 LRV 23.4   L* 55.49</div>	 <div>Powder Pink 04800 LRV 30.1   L* 61.73</div>	 <div>Midnight Powder 04801 LRV 11.4   L* 40.3</div>	 <div>Copper 04865 LRV 18.9   L* 50.61</div>	 <div>Rosewood 04870 LRV 18.8   L* 50.47</div>

Additional Information

\*\*Manufactured in ISO 9001 certified facility. Meets or exceeds all local and national regulations in country of manufacture.

[Installation Guidelines](#)

[15 Year Commercial Limited warranty](#)

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

