

Stijlnummer	C040W	
Collectie	Floor Architecture III	
Producttype	Tapijttegel	
Construction	Standard	Data + Performance
Type Fabricage	ISO 2424	tufted 1/10"   39.4 per 10cm
Uitzicht	ISO 2424	Multilevel-Patroonlus
Verfmethode	EN 994	100% In Oplossing Geverfd
Productformaat	EN 994	50 cm x 50 cm   16 tiles (4 m²) per box
Primaire Backing	ISO 2424	Pet Nonwoven
Secundaire Backing	ISO 2424	Comfortworx® Tegel   Matrix Padlaag Bevat 90% Gerecycleerd Materiaal
Vezel	ISO 2424	Ecosolution Q® Polyamide 6
Totale Dikte	ISO 1765	11.1 mm
Afgewerkte Pooldikte	ISO 1766	2.8 mm
Totale Massa	ISO 8543	4069 g/m²
Getuft Gewicht	ISO 2424	630 g/m²
Effectieve Poolmassa	ISO 8543	308 g/m²
Pooldichtheid	ISO 8543	0.109 g/cm³
Totaal Gerecycleerde Inhoud		57% (pre-consumer 45%   post-consumer 12%)

Gegevens

Steken	ISO 1763	165,000/m²   42 per 10cm
Elektrostatische Weerstand	ISO 6356	≤ 2.0 kv (Stroll Test)
Gebruik Classificatie	EN 1307	33 Commercial Heavy
Luxeklasse	EN 1307	LC1
Dimensionale Stabiliteit	EN 986	≤ 0.2%
Contactgeluidsisolatie	ISO 10140	37db
Geluidsabsorptieclassificatie	ISO 354/11654	0.30 Aw   Class D
Warmteweerstand m² K/w	ISO 8302	0.179 M² K/W Tog 1.79
Weerstand Tegen Droog Uitglijden	ISO 13893	Pass / No Pulled Loops
Kleurvastheid Voor Licht	ISO 105-B02	>6
Ontvlambaarheid	EN 13501-1	Bfl-S1 (Adhered Testing)
Stoel Met Wieltjes	EN 985	≥2.4 Continuous USE

15 Jaar Commercieel Beperkt subject to installation in full accordance with the manufacturer's instructions and a regular effective cleaning and maintenance programme. Second location warranties are available with the use of non-adhesive IOBAC Magtabs and Tabit accessories.

Aanbevolen Installatiemethode

Monolithic

Quarter Turn

Brick

Ashlar

Random

37dB

Coördinerende Producten

Carpet Tile: **Stone Comfortworx® Tile, Fragment Comfortworx® Tile, Formation Colours Comfortworx® Tile, Fragment Colours Comfortworx® Tile, Formation Comfortworx® Tile, Fragment Taskworx® Tile, Stone Taskworx® Tile, Formation Colours Ecoworx S® Tile, Fragment Colours Ecoworx S® Tile, Formation Colours Taskworx® Tile, Fragment Colours Taskworx® Tile, Fragment Ecoworx S® Tile, Stone Ecoworx S® Tile, Formation Taskworx® Tile, Formation Ecoworx S® Tile, Stone Colours Taskworx® Tile, Stone Colours Ecoworx S® Tile**

Kenmerken + Certificeringen

Environmental Product Declaration (EPD)

milieugarantie  
ISO 9001  
land van herkomst  
BREEAM Contribution Credit

3de Partij Gecertificeerd in Overeenstemming Met ISO14044, ISO14025 & EN15804  
Take Back Policy Offered For All Comfortworx Products  
Gecertificeerd  
Verenigd Koninkrijk  
Certificate of Approval  
Schools/Offices/Health/Industrial Shed  
Retail

Well V2 Contribution Credit

X11 Langetermijn-emissiebeheersing - deel 2: Optimalisering van vloeren - 1 pt **M1> Emissions Class For Building Material**

Groen Leed Bijdragekrediet

"MR-krediet: openbaarmaking en optimalisering van bouwproducten  
Milieuproductverklaringen - Optie 1: Milieuproductverklaring (EPD)"  
"MR-krediet: Openbaarmaking en optimalisering van bouwproducten  
Materiaal ingrediënten - Optie 1: Rapportage materiaal ingrediënten"







3rd Party Certified in Accordance with ISO14044, ISO14025 & EN15804  
HPD ( Version 2.1 )












Memberships

WGBC Framework  
UKGBC  
Emirates Green Building Council  
Chemsec

WGBC Framework  
UKGBC  
Emirates Green Building Council  
Chemsec

Lichtreflectiewaarde

					
Oatmeal 04111 LRV 31.9   L* 63.25	Brushed Gold 04210 LRV 24.6   L* 56.69	Midnight Brushed 04211 LRV 8.1   L* 34.2	Mineral 04327 LRV 22.9   L* 54.94	Midnight Mineral 04328 LRV 12.5   L* 42.02	Racing Green 04334 LRV 6.2   L* 29.9

					
Sage 04375 LRV 22.3   L* 54.39	Midnight Sage 04376 LRV 7.5   L* 32.97	Sky 04411 LRV 24.9   L* 56.96	Midnight Sky 04412 LRV 9.6   L* 37.08	Steel Blue 04447 Denim 04486 LRV 10   L* 37.8	
					
Midnight Apricot 04674 LRV 7.8   L* 33.46	Apricot 04675 LRV 23.4   L* 55.49	Powder Pink 04800 LRV 30.1   L* 61.73	Midnight Powder 04801 LRV 11.4   L* 40.3	Copper 04865 LRV 18.9   L* 50.61	Rosewood 04870 LRV 18.8   L* 50.47

Aanvullende Informatie

\*\*Manufactured in ISO 9001 certified facility. Meets or exceeds all local and national regulations in country of manufacture.

[Installation Guidelines](#)

[15 jaar commercieel beperkt](#)

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

