# ShawContract®

## Central 6 X 12 Covebase Matte

*PVC-Free*

| | |
|---|---|
| Style Number | **CT11K** |
| Composition | **Porcelain** |
| Tile Type | **Covebase** |
| Body Type | **Glazed Porcelain** |
| Finish | **Matte** |
| Nominal Dimensions | **6" x 12" \| 15.24 cm x 30.48 cm** |
| Actual Dimensions | **6.42" x 11.75" \| 16.3 cm x 29.85 cm** |
| Overall Thickness | **0.314" \| 8 mm** |
| Edge Profile | **Cut** |
| Country Of Origin | **United States** |
| Installation Area | **Walls** |
| Retail Unit Of Measure | **Sold by the individual piece** |



### Packaging

| | |
|---|---|
| Pieces per Carton | **8** |
| Area per Carton | **3.88 ft²** |
| Area per Pallet | **194 ft²** |
| Boxes per Pallet | **50 boxes** |

### Performance + Testing

| | |
|---|---|
| Shade Variation | **V2** |
| Breaking Strength (ASTM C648) | ≥ **125 lbf** |
| DCOF | ≥ **0.42** |
| Scratch Hardness (ASTM MOHS) | **7** |

### Warranties

1 Year Commercial Limited Warranty

### Available Colorways


110 Rest


125 Villa


540 Steel


595 Ore


775 Aroma

230 Douthit Ferry Road | Cartersville GA 30120 | USA | 1 800.257.7429 | shawcontract.com

For reference purposes only if printed or downloaded.

## Additional Information

Per ANSI A326.3, a DCOF of ≥ 0.42 is recommended for tiles in commercial applications. Tiles with a DCOF < 0.42 are not recommended for wet or slippery areas. Contaminants like water, oil, or grease can increase slip risk—use caution when selecting products for such environments. For approved Areas of Application, please reference the chart above. For more information, visit www.tcnatile.com.

Not for use on ramps.

Due to natural variation in ceramic and porcelain tile, final selection should be based on actual product samples.

Ceramic Porcelain Step by Step Installation
Maintenance Guidelines

CERTIFIED PORCELAIN TILE 0.5% or less water absorption

Made in the USA



For reference purposes only if printed or downloaded.