

## Exclusive 12X24 Polished

Style Number	CT15K
Composition	Porcelain
Tile Type	Floor
Body Type	Glazed Color Body Porcelain
Finish	Polished
Nominal Dimensions	12" x 24"   30 cm x 60 cm
Actual Dimensions	11.75" x 23.75"   29.85 cm x 60.33 cm
Overall Thickness	0.314"   8 mm
Edge Profile	Rectified
Country Of Origin	United States
Installation Area	Floors, Walls

### Packaging

Pieces per Carton	8
Area per Carton	15.75 sq ft   1.46 sq m
Weight per Carton	58.07 lbs   26.34 kg

### Performance + Testing

Shade Variation	V2
Breaking Strength	≥ 250 lbs
Water Absorption %	≤ 0.50% (Impervious (Porcelain))
DCOF	< 0.42



### Warranties

[1 Year Commercial Limited Warranty](#)

### Available Colorways



105 Luxury



110 Luna

### Additional Information

---

A DCOF value of  $\geq 0.42$  is the standard for tiles specified for commercial applications as stated in standard ANSI 326.3. For more information, visit the Tile Council of North America's website: [www.tcnatile.com](http://www.tcnatile.com)

Tiles with a DCOF value less than 0.42 are not recommended for use in areas with wet or slippery conditions.

Water, oil, grease and other contaminants can create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection.

Not for use on ramps.

Since there are variations in all fired ceramic and porcelain products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation.

[Ceramic Porcelain Step By Step Installation](#)

[Maintenance Guidelines](#)

