ShawContract®

Varietal 3 X 12 Bullnose Matte

PVC-Free

Style Number	**CT03K**
Composition	**Porcelain**
Tile Type	**Bullnose**
Body Type	**Glazed Porcelain**
Finish	**Matte**
Nominal Dimensions	**3" x 12" | 7.62 cm x 30.48 cm**
Actual Dimensions	**3" x 12" | 7.62 cm x 30.48 cm**
Overall Thickness	**0.314" | 8 mm**
Edge Profile	**Cut**
Country Of Origin	**United States**
Installation Area	**Walls**
Retail Unit Of Measure	**Sold by the individual piece**



Packaging

Pieces per Carton	**36**
Area per Carton	**9 ft²**
Weight per Carton	**32.8 lbs**
Area per Pallet	**720 ft²**
Boxes per Pallet	**80 boxes**

Performance + Testing

Shade Variation	**V2**
Breaking Strength (ASTM C648)	≥ **250 lbf**
Water Absorption (ASTM C373) %	≤ **0.50% (Impervious (Porcelain))**
DCOF	≥ **0.42**
Wear Rating	***4 (Heavy Traffic)**

*Designed for commercial areas with regular foot traffic and normal footwear.

Warranties

1 Year Commercial Limited Warranty

Available Colorways



100 Calm



101 Almond



500 Haze



900 Midnight

For reference purposes only if printed or downloaded.

Additional Information

Per ANSI A326.3, a DCOF of ≥ 0.42 is recommended for tiles in commercial applications. Tiles with a DCOF < 0.42 are not recommended for wet or slippery areas. Contaminants like water, oil, or grease can increase slip risk—use caution when selecting products for such environments. For approved Areas of Application, please reference the chart above. For more information, visit www.tcnatile.com.

Not for use on ramps.

Due to natural variation in ceramic and porcelain tile, final selection should be based on actual product samples.

Ceramic Porcelain Step by Step Installation
Maintenance Guidelines

CERTIFIED PORCELAIN TILE 0.5% or less water absorption

Made in the USA

For reference purposes only if printed or downloaded.