

## Simply Slated 12 X 24 Matte

Style Number	<b>CT07K</b>
Composition	<b>Porcelain</b>
Tile Type	<b>Floor</b>
Body Type	<b>Glazed Color Body Porcelain</b>
Nominal Dimensions	<b>12" x 24"   30 cm x 60 cm</b>
Actual Dimensions	<b>11.75" x 23.75"   29.85 cm x 60.33 cm</b>
Overall Thickness	<b>0.314"   8 mm</b>
Edge Profile	<b>Rectified</b>
Country Of Origin	<b>United States</b>
Installation Area	<b>Floors, Walls</b>

### Packaging

Pieces per Carton	<b>8</b>
Area per Carton	<b>15.5 sq ft   1.44 sq m</b>
Weight per Carton	<b>58.07 lbs   26.34 kg</b>

### Performance + Testing


Breaking Strength	<b>≥ 250 lbs</b>
Water Absorption %	<b>≤ 0.50% (Impervious (Porcelain))</b>
DCOF	<b>≥ 0.42</b>



### Warranties

[1 Year Commercial Limited Warranty](#)

### Available Colorways



500 Mist

550 Stone Gray

580 Shadow

780 Decaf

790 Hound

### Additional Information

---

A DCOF value of  $\geq 0.42$  is the standard for tiles specified for commercial applications as stated in standard ANSI 326.3. For more information, visit the Tile Council of North America's website: [www.tcnatile.com](http://www.tcnatile.com).

Tiles with a DCOF value less than 0.42 are not recommended for use in areas with wet or slippery conditions.

Water, oil, grease, and other contaminants can create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection.

Not for use on ramps.

Since there are variations in all fired ceramic and porcelain products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation.

[Ceramic Porcelain Step By Step Installation](#)

[Maintenance Guidelines](#)

