ShawContract®

Tempo 3 X 14 Matte

PVC-Free

Style Number	**CT21L**
Composition	**Ceramic**
Tile Type	**Wall Tile**
Body Type	**Glazed Ceramic**
Finish	**Matte**
Nominal Dimensions	**4" x 15" | 9 cm x 37 cm**
Actual Dimensions	**3.61" x 14.65" | 9.17 cm x 37.21 cm**
Overall Thickness	**0.314" | 8 mm**
Edge Profile	**Pressed**
Country Of Origin	**Brazil**
Retail Unit Of Measure	**Sold by the box quantity**
Number of Faces	**1**



Packaging

Pieces per Carton	**20**
Area per Carton	**7.35 ft²**
Weight per Carton	**27.56 lbs**
Area per Pallet	**617.4 ft²**
Boxes per Pallet	**84 boxes**

Recommended Installation Method

Offset Requirements: For a running bond / brick / staggered installation methods. Tiles with a side larger than 15": 33% offset or less.Tiles with a side smaller than 15": 50% offset of less.

Grout Joint Requirement: Minimum of 3/16"

Performance + Testing

Shade Variation	**V1**
Breaking Strength (ASTM C648)	≥ **250 lbf**
Water Absorption (ASTM C373) %	**> 0.50% (Vitreous)**
DCOF	≥ **0.42**
Scratch Hardness (ASTM MOHS)	**7**
Frost Resistance (ASTM C1026)	**Not Resistant**
Wear Rating	***0 (Walls Only)**

*Not suitable for floors. Use only on walls or vertical surfaces.

Areas of Application

Interior Walls/Backsplash	✔	Interior Wet Plus	
Interior Dry Floors		Exterior Wet Floors	
Interior Wet Floors		Exterior Walls	
Shower Floors		Oils / Grease	

Warranties

1 Year Commercial Limited Warranty

For reference purposes only if printed or downloaded.

ShawContract®

Tempo 3 X 14 Matte

Available Colorways

100 Serene


370 Upbeat


485 Steady


675 Vivo


855 Mellow


870 Rapido

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Additional Information

Per ANSI A326.3, a DCOF of ≥ 0.42 is recommended for tiles in commercial applications. Tiles with a DCOF < 0.42 are not recommended for wet or slippery areas. Contaminants like water, oil, or grease can increase slip risk—use caution when selecting products for such environments. For approved Areas of Application, please reference the chart above. For more information, visit www.tcnatile.com.

Not for use on ramps.

Due to natural variation in ceramic and porcelain tile, final selection should be based on actual product samples.

Ceramic Porcelain Step by Step Installation
Maintenance Guidelines

For reference purposes only if printed or downloaded.