ShawContract®

Petra 6 X 12 Covebase

PVC-Free

Style Number	**CT28L**
Composition	**Porcelain**
Tile Type	**Covebase**
Body Type	**Colorbody Glazed Porcelain**
Finish	**Matte**
Nominal Dimensions	**6" x 12" | 15.24 cm x 30.48 cm**
Actual Dimensions	**5.85" x 11.75" | 14.86 cm x 29.85 cm**
Overall Thickness	**0.275" | 7 mm**
Edge Profile	**Cut**
Country Of Origin	**United States**
Retail Unit Of Measure	**Sold by the individual piece**

Packaging

Pieces per Carton	**20**
Weight per Carton	**30.5 lbs**
Area per Pallet	**68 ft²**
Boxes per Pallet	**68 boxes**

Performance + Testing

Shade Variation	**V2**
Breaking Strength (ASTM C648)	≥ **275 lbf**
Water Absorption (ASTM C373) %	≤ **0.50% (Impervious (Porcelain))**
Scratch Hardness (ASTM MOHS)	**6**
Wear Rating	***0 (Walls Only)**

*Not suitable for floors. Use only on walls or vertical surfaces.

Warranties

1 Year Commercial Limited Warranty


Available Colorways



111 Overcast



504 Shadow



760 Storm

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

For reference purposes only if printed or downloaded.

Additional Information

Per ANSI A326.3, a DCOF of ≥ 0.42 is recommended for tiles in commercial applications. Tiles with a DCOF < 0.42 are not recommended for wet or slippery areas. Contaminants like water, oil, or grease can increase slip risk—use caution when selecting products for such environments. For approved Areas of Application, please reference the chart above. For more information, visit www.tcnatile.com.

Not for use on ramps.

Due to natural variation in ceramic and porcelain tile, final selection should be based on actual product samples.

Ceramic Porcelain Step by Step Installation
Maintenance Guidelines

For reference purposes only if printed or downloaded.