ShawContract®

Connector Subway Speckle

PVC-Free

Style Number	**CT50L**
Composition	**Porcelain**
Tile Type	**Subway Tile**
Body Type	**Glazed Porcelain**
Finish	**Speckle**
Nominal Dimensions	**2.4" x 9.8" | 6.1 cm x 24.89 cm**
Actual Dimensions	**2.4" x 9.8" | 6.1 cm x 24.89 cm**
Overall Thickness	**0.393" | 10 mm**
Edge Profile	**Pressed**
Country Of Origin	**Italy**
Installation Area	**Walls, Floors**
Retail Unit Of Measure	**Sold by the box quantity**
Number of Faces	**4**



Packaging

Pieces per Carton	**38**
Area per Carton	**6.13 ft²**
Weight per Carton	**28 lbs**
Area per Pallet	**416.84 ft²**
Boxes per Pallet	**68 boxes**

Recommended Installation Method

Grout Joint Requirement: Minimum of 3/16"

Offset Requirements: For a running bond / brick / staggered installation methods. Tiles with a side larger than 15": 33% offset or less.Tiles with a side smaller than 15": 50% offset of less.

Performance + Testing

Shade Variation	**V3**
Breaking Strength (ASTM C648)	≥ **250 lbf**
Water Absorption (ASTM C373) %	≤ **0.50% (Impervious (Porcelain))**
DCOF	≥ **0.42**
Scratch Hardness (ASTM MOHS)	**6**
Frost Resistance (ASTM C1026)	**Resistant**
Chemical Resistance (ASTM C650)	**Class A**
Stain Resistance (ASTM C1378)	**Class A**
Wear Rating	***3 (Moderate Traffic)**

*Suitable for most residential spaces and light commercial use.

Areas of Application

Interior Walls/Backsplash	✔	Interior Wet Plus	✔
Interior Dry Floors	✔	Exterior Wet Floors	
Interior Wet Floors	✔	Exterior Walls	✔
Shower Floors	✔	Oils / Grease	

For reference purposes only if printed or downloaded.

ShawContract®

Connector Subway Speckle

Warranties

1 Year Commercial Limited Warranty

Available Colorways


100 Framework


105 Build Beige


155 Technic Tan


200 Layer Yellow


370 Gearbox Green


429 Bridge Blue


500 Geometry Grey


505 Cube Black


740 Base Brown


800 Puzzle Pink


855 Robo Red

CERTIFIED PORCELAIN TILE™
0.5% or less water absorption

230 Douthit Ferry Road | Cartersville GA 30120 | USA | 1 800.257.7429 | shawcontract.com

For reference purposes only if printed or downloaded.

Additional Information

Per ANSI A326.3, a DCOF of ≥ 0.42 is recommended for tiles in commercial applications. Tiles with a DCOF < 0.42 are not recommended for wet or slippery areas. Contaminants like water, oil, or grease can increase slip risk—use caution when selecting products for such environments. For approved Areas of Application, please reference the chart above. For more information, visit www.tcnatile.com.

Not for use on ramps.

Due to natural variation in ceramic and porcelain tile, final selection should be based on actual product samples.

Ceramic Porcelain Step by Step Installation
Maintenance Guidelines

CERTIFIED PORCELAIN TILE™
0.5% or less water absorption

For reference purposes only if printed or downloaded.