ShawContract®

Graphline 24 x 48 Wall Panel

PVC-Free

Style Number	**CT53L**
Composition	**Porcelain**
Tile Type	**Wall Panel**
Body Type	**Glazed Porcelain**
Finish	**Matte**
Nominal Dimensions	**24" x 48" | 60.96 cm x 121.92 cm**
Actual Dimensions	**23.5" x 47.09" | 59.7 cm x 119.6 cm**
Overall Thickness	**0.374" | 9.5 mm**
Edge Profile	**Rectified**
Country Of Origin	**Italy**
Installation Area	**Walls**
Retail Unit Of Measure	**Sold by the box quantity**
Number of Faces	**1**



Packaging

Pieces per Carton	**2**
Area per Carton	**15.5 ft²**
Weight per Carton	**68.34 lbs**
Area per Pallet	**604.5 ft²**
Boxes per Pallet	**39 boxes**

Recommended Installation Method

Grout Joint Requirement: Minimum of 1/8"

Offset Requirements: For a running bond / brick / staggered installation methods. Tiles with a side larger than 15": 33% offset or less.Tiles with a side smaller than 15": 50% offset of less.

Performance + Testing

Shade Variation	**V2**
Breaking Strength (ASTM C648)	≥ **250 lbf**
Water Absorption (ASTM C373) %	≤ **0.50% (Impervious (Porcelain))**
Frost Resistance (ASTM C1026)	**Resistant**
Chemical Resistance (ASTM C650)	**Class A**
Stain Resistance (ASTM C1378)	**Class 5**
Wear Rating	***0 (Walls Only)**

*Not suitable for floors. Use only on walls or vertical surfaces.

Areas of Application

Interior Walls/Backsplash	✔	Interior Wet Plus	
Interior Dry Floors		Exterior Wet Floors	
Interior Wet Floors		Exterior Walls	
Shower Floors		Oils / Grease	

For reference purposes only if printed or downloaded.


ShawContract®

Graphline 24 x 48 Wall Panel


Warranties

1 Year Commercial Limited Warranty


Available Colorways




100 Framework White




370 Gearbox Green




429 Bridge Blue



505 Cube Black



675 Venture Orange



855 Robo Red

Additional Information

Per ANSI A326.3, a DCOF of ≥ 0.42 is recommended for tiles in commercial applications. Tiles with a DCOF < 0.42 are not recommended for wet or slippery areas. Contaminants like water, oil, or grease can increase slip risk—use caution when selecting products for such environments. For approved Areas of Application, please reference the chart above. For more information, visit www.tcnatile.com.

Not for use on ramps.

Due to natural variation in ceramic and porcelain tile, final selection should be based on actual product samples.

Ceramic Porcelain Step by Step Installation
Maintenance Guidelines

CERTIFIED PORCELAIN™ TILE
0.5% or less water absorption

230 Douthit Ferry Road | Cartersville GA 30120 | USA | 1 800.257.7429 | shawcontract.com

For reference purposes only if printed or downloaded.