ShawContract®

Dusk 3 X 24 Bullnose

PVC-Free

Style Number	**CT75K**
Composition	**Porcelain**
Tile Type	**Bullnose**
Body Type	**Colorbody Glazed Porcelain**
Finish	**Matte**
Nominal Dimensions	**3" x 24" | 7.62 cm x 60.96 cm**
Actual Dimensions	**2.8" x 23.46" | 7.1 cm x 59.6 cm**
Overall Thickness	**0.354" | 9 mm**
Edge Profile	**Cut**
Country Of Origin	**United States**
Installation Area	**Walls**
Retail Unit Of Measure	**Sold by the individual piece**

Packaging

Pieces per Carton	**10**
Area per Carton	**4.65 ft^2**
Weight per Carton	**18 lbs**
Area per Pallet	**325.5 ft^2**
Boxes per Pallet	**70 boxes**

Performance + Testing

Shade Variation	**V2**
Water Absorption (ASTM C373) %	≤ **0.50% (Impervious (Porcelain))**

Material Health & Environmental Certifications


Health & Wellbeing - Material & Ingredient Transparency

Health Product Declaration (HPD) — 1000 ppm Disclosure

Warranties

1 Year Commercial Limited Warranty


Available Colorways



505 Inkwell



515 Moonglow



535 Mist

For reference purposes only if printed or downloaded.

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Additional Information

Per ANSI A326.3, a DCOF of ≥ 0.42 is recommended for tiles in commercial applications. Tiles with a DCOF < 0.42 are not recommended for wet or slippery areas. Contaminants like water, oil, or grease can increase slip risk—use caution when selecting products for such environments. For approved Areas of Application, please reference the chart above. For more information, visit www.tcnatile.com.

Not for use on ramps.

Due to natural variation in ceramic and porcelain tile, final selection should be based on actual product samples.

Ceramic Porcelain Step by Step Installation
Maintenance Guidelines

For reference purposes only if printed or downloaded.