# ShawContract®

## Cemented 12 X 24 Matte

*PVC-Free*

| | |
|---|---|
| Style Number | **CT78J** |
| Composition | **Porcelain** |
| Tile Type | **Field Tile** |
| Body Type | **Colorbody Glazed Porcelain** |
| Finish | **Matte** |
| Nominal Dimensions | **12" x 24" \| 30.48 cm x 60.96 cm** |
| Actual Dimensions | **11.73" x 23.58" \| 29.8 cm x 59.9 cm** |
| Overall Thickness | **0.314" \| 8 mm** |
| Edge Profile | **Rectified** |
| Country Of Origin | **United States** |
| Installation Area | **Floors, Walls** |
| Retail Unit Of Measure | **Sold by the box quantity** |



### Packaging

| | |
|---|---|
| Pieces per Carton | **6** |
| Area per Carton | **12 ft²** |
| Weight per Carton | **52.8 lbs** |
| Area per Pallet | **576 ft²** |
| Boxes per Pallet | **48 boxes** |

### Performance + Testing

| | |
|---|---|
| Shade Variation | **V2** |
| Breaking Strength (ASTM C648) | ≥ **250 lbf** |
| Water Absorption (ASTM C373) % | ≤ **0.50% (Impervious (Porcelain))** |
| DCOF | ≥ **0.42** |
| Wear Rating | ***4 (Heavy Traffic)** |

*Designed for commercial areas with regular foot traffic and normal footwear.

### Areas of Application

| | | | |
|---|---|---|---|
| Interior Walls/Backsplash | ✔ | Interior Wet Plus | |
| Interior Dry Floors | ✔ | Exterior Wet Floors | |
| Interior Wet Floors | ✔ | Exterior Walls | ✔ |
| Shower Floors | | Oils / Grease | |

### Warranties

1 Year Commercial Limited Warranty



For reference purposes only if printed or downloaded.

# ShawContract®

# Cemented 12 X 24 Matte

## Available Colorways


100 Salt


110 Tundra


450 Smoky Blue


560 Atmosphere


570 Thunder


595 Galaxy

## Additional Information

Per ANSI A326.3, a DCOF of ≥ 0.42 is recommended for tiles in commercial applications. Tiles with a DCOF < 0.42 are not recommended for wet or slippery areas. Contaminants like water, oil, or grease can increase slip risk—use caution when selecting products for such environments. For approved Areas of Application, please reference the chart above. For more information, visit www.tcnatile.com.

Not for use on ramps.

Due to natural variation in ceramic and porcelain tile, final selection should be based on actual product samples.

Ceramic Porcelain Step by Step Installation
Maintenance Guidelines

CERTIFIED PORCELAIN TILE™
0.5% or less water absorption

Made in the USA

230 Douthit Ferry Road | Cartersville GA 30120 | USA | 1 800.257.7429 | shawcontract.com

For reference purposes only if printed or downloaded.