ShawContract®

Format 6 X 12 Covebase

PVC-Free

Style Number	**CT66L**
Composition	**Ceramic**
Tile Type	**Covebase**
Body Type	**Colorbody Porcelain**
Finish	**Matte**
Nominal Dimensions	**6" x 12" | 15.24 cm x 30.48 cm**
Actual Dimensions	**6.42" x 11.75" | 16.3 cm x 29.85 cm**
Overall Thickness	**0.275" | 7 mm**
Edge Profile	**Cut**
Country Of Origin	**United States**
Installation Area	**Walls**
Retail Unit Of Measure	**Sold by the individual piece**

Packaging

Pieces per Carton	**20**
Area per Carton	**9.69 ft^2**
Weight per Carton	**30.9 lbs**
Area per Pallet	**620.16 ft^2**
Boxes per Pallet	**64 boxes**

Performance + Testing

Shade Variation	**V2**
Breaking Strength (ASTM C648)	≥ **250 lbf**
Water Absorption (ASTM C373) %	≤ **0.50% (Impervious (Porcelain))**
Scratch Hardness (ASTM MOHS)	**7**
Frost Resistance (ASTM C1026)	**Resistant**
Chemical Resistance (ASTM C650)	**Class A**
Stain Resistance (ASTM C1378)	**Class A**
Wear Rating	***4 (Heavy Traffic)**

*Designed for commercial areas with regular foot traffic and normal footwear.

Material Health & Environmental Certifications

Health & Wellbeing - Material & Ingredient Transparency

Health Product Declaration (HPD) — 1000 ppm Disclosure

Warranties

1 Year Commercial Limited Warranty

For reference purposes only if printed or downloaded.

ShawContract®

Format 6 X 12 Covebase

Available Colorways

100 Bright White


110 Sand


125 Khaki


211 Brass


395 Meadow


415 Bluebell


429 Lapis


500 Dune


505 Midnight


520 Pure Gray


540 Slate


595 Graphite


715 Brick

Additional Information

Per ANSI A326.3, a DCOF of ≥ 0.42 is recommended for tiles in commercial applications. Tiles with a DCOF < 0.42 are not recommended for wet or slippery areas. Contaminants like water, oil, or grease can increase slip risk—use caution when selecting products for such environments. For approved Areas of Application, please reference the chart above. For more information, visit www.tcnatile.com.

Not for use on ramps.

Due to natural variation in ceramic and porcelain tile, final selection should be based on actual product samples.

Ceramic Porcelain Step by Step Installation
Maintenance Guidelines

For reference purposes only if printed or downloaded.