ShawContract®

Inspired Onyx 3 X 12 Bullnose Polished

PVC-Free

Style Number	**CT65J**
Composition	**Porcelain**
Tile Type	**Bullnose**
Body Type	**Colorbody Glazed Porcelain**
Finish	**Polished**
Nominal Dimensions	**3" x 12" | 7.62 cm x 30.48 cm**
Actual Dimensions	**2.75" x 11.61" | 6.99 cm x 29.5 cm**
Overall Thickness	**0.314" | 8 mm**
Edge Profile	**Cut**
Country Of Origin	**United States**
Installation Area	**Walls**
Retail Unit Of Measure	**Sold by the individual piece**



Packaging

Pieces per Carton	**36**
Area per Carton	**9 ft²**
Weight per Carton	**35.68 lbs**
Area per Pallet	**720 ft²**
Boxes per Pallet	**80 boxes**

Performance + Testing

Shade Variation	**V3**
Breaking Strength (ASTM C648)	≥ **400 lbf**
Water Absorption (ASTM C373) %	≤ **0.50% (Impervious (Porcelain))**
DCOF	≥ **0.42**
Wear Rating	***3 (Moderate Traffic)**

*Suitable for most residential spaces and light commercial use.

Warranties

1 Year Commercial Limited Warranty

Available Colorways



100 White

152 Ivory



200 Beige



550 Dark Grey

230 Douthit Ferry Road | Cartersville GA 30120 | USA | 1 800.257.7429 | shawcontract.com

For reference purposes only if printed or downloaded.

Additional Information

Per ANSI A326.3, a DCOF of ≥ 0.42 is recommended for tiles in commercial applications. Tiles with a DCOF < 0.42 are not recommended for wet or slippery areas. Contaminants like water, oil, or grease can increase slip risk—use caution when selecting products for such environments. For approved Areas of Application, please reference the chart above. For more information, visit www.tcnatile.com.

Not for use on ramps.

Due to natural variation in ceramic and porcelain tile, final selection should be based on actual product samples.

Ceramic Porcelain Step by Step Installation
Maintenance Guidelines

CERTIFIED PORCELAIN TILE 0.5% or less water absorption

Made in the USA

For reference purposes only if printed or downloaded.