ShawContract®

Pulse 6 X 6 Interval Matte

PVC-Free

Style Number	**CT95K**
Composition	**Ceramic**
Tile Type	**Mosaic**
Body Type	**Glazed Ceramic**
Finish	**Matte**
Nominal Dimensions	**6" x 6" | 15.24 cm x 15.24 cm**
Actual Dimensions	**5.91" x 5.91" | 15.01 cm x 15.01 cm**
Overall Thickness	**0.314" | 8 mm**
Edge Profile	**Cut**
Country Of Origin	**United States**
Installation Area	**Walls**
Retail Unit Of Measure	**Sold by the individual piece**



Packaging

Pieces per Carton	**20**
Area per Carton	**4.8 ft²**
Weight per Carton	**18.46 lbs**
Area per Pallet	**230.4 ft²**
Boxes per Pallet	**48 boxes**

Performance + Testing

Shade Variation	**V3**
Breaking Strength (ASTM C648)	≥ **125 lbf**
Water Absorption (ASTM C373) %	**> 0.50% (Vitreous)**
DCOF	≥ **0.42**
Scratch Hardness (ASTM MOHS)	**7**
Frost Resistance (ASTM C1026)	**Resistant**
Chemical Resistance (ASTM C650)	**Class A**
Stain Resistance (ASTM C1378)	**Class A**
Wear Rating	***0 (Walls Only)**

*Not suitable for floors. Use only on walls or vertical surfaces.

Areas of Application

Interior Walls/Backsplash	✔	Interior Wet Plus	
Interior Dry Floors		Exterior Wet Floors	
Interior Wet Floors		Exterior Walls	✔
Shower Floors		Oils / Grease	

For reference purposes only if printed or downloaded.

ShawContract®

Pulse 6 X 6 Interval Matte

Warranties

1 Year Commercial Limited Warranty

Available Colorways


105 Nova


137 Nova Upbeat


142 Nova Steady


153 Samba Upbeat


154 Samba Steady


155 Samba


158 Samba Rapido


187 Nova Rapido


537 Echo Upbeat


542 Echo Steady


580 Echo


587 Echo Rapido


737 Vento Upbeat


742 Vento Steady


761 Vento


787 Vento Rapido

For reference purposes only if printed or downloaded.

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Additional Information

Per ANSI A326.3, a DCOF of ≥ 0.42 is recommended for tiles in commercial applications. Tiles with a DCOF < 0.42 are not recommended for wet or slippery areas. Contaminants like water, oil, or grease can increase slip risk—use caution when selecting products for such environments. For approved Areas of Application, please reference the chart above. For more information, visit www.tcnatile.com.

Not for use on ramps.

Due to natural variation in ceramic and porcelain tile, final selection should be based on actual product samples.

Ceramic Porcelain Step by Step Installation
Maintenance Guidelines

For reference purposes only if printed or downloaded.