# ShawContract®

## Simple 3 X 6 Glossy

*PVC-Free*

| | |
|---|---|
| Style Number | **CT95J** |
| Composition | **Ceramic** |
| Tile Type | **Wall Tile** |
| Body Type | **Glazed Ceramic** |
| Finish | **Gloss** |
| Nominal Dimensions | **3" x 6" \| 7.62 cm x 15.24 cm** |
| Actual Dimensions | **2.95" x 5.91" \| 7.5 cm x 15 cm** |
| Overall Thickness | **0.275" \| 7 mm** |
| Edge Profile | **Pressed** |
| Country Of Origin | **Turkey** |
| Installation Area | **Walls** |
| Retail Unit Of Measure | **Sold by the box quantity** |



### Packaging

| | |
|---|---|
| Pieces per Carton | **88** |
| Area per Carton | **10.66 ft²** |
| Weight per Carton | **27.37 lbs** |
| Area per Pallet | **724.88 ft²** |
| Boxes per Pallet | **68 boxes** |

### Recommended Installation Method

Grout Joint Requirement: Minimum of 3/16"

Offset Requirements: For a running bond / brick / staggered installation methods. Tiles with a side larger than 15": 33% offset or less.Tiles with a side smaller than 15": 50% offset of less.

### Performance + Testing

| | |
|---|---|
| Shade Variation | **V1** |
| Breaking Strength (ASTM C648) | ≥ **100 lbf** |
| Water Absorption (ASTM C373) % | **> 0.50% (Non Vitreous)** |
| Scratch Hardness (ASTM MOHS) | **2** |
| Frost Resistance (ASTM C1026) | **Not Resistant** |
| Chemical Resistance (ASTM C650) | **Class B** |
| Stain Resistance (ASTM C1378) | **Class B** |

### Areas of Application

| | | | |
|---|---|---|---|
| Interior Walls/Backsplash | ✔ | Interior Wet Plus | |
| Interior Dry Floors | | Exterior Wet Floors | |
| Interior Wet Floors | | Exterior Walls | |
| Shower Floors | | Oils / Grease | |

### Warranties

1 Year Commercial Limited Warranty





For reference purposes only if printed or downloaded.


# ShawContract®

## Simple 3 X 6 Glossy


### Available Colorways



100 White


300 Sage


400 Glacier


500 Warm Grey


550 Cement Chic


950 Carbon

### Additional Information

Per ANSI A326.3, a DCOF of ≥ 0.42 is recommended for tiles in commercial applications. Tiles with a DCOF < 0.42 are not recommended for wet or slippery areas. Contaminants like water, oil, or grease can increase slip risk—use caution when selecting products for such environments. For approved Areas of Application, please reference the chart above. For more information, visit www.tcnatile.com.

Not for use on ramps.

Due to natural variation in ceramic and porcelain tile, final selection should be based on actual product samples.

Ceramic Porcelain Step by Step Installation
Maintenance Guidelines



For reference purposes only if printed or downloaded.