# ShawContract®

## Simple 4 X 16 Bullnose Glossy

*PVC-Free*

| | |
|---|---|
| Style Number | **CT97J** |
| Composition | **Ceramic** |
| Tile Type | **Bullnose** |
| Body Type | **Glazed Ceramic** |
| Finish | **Gloss** |
| Nominal Dimensions | **4" x 16" \| 10.16 cm x 40.64 cm** |
| Actual Dimensions | **3.94" x 15.75" \| 10 cm x 40 cm** |
| Overall Thickness | **0.314" \| 8 mm** |
| Edge Profile | **Cut** |
| Country Of Origin | **Turkey** |
| Installation Area | **Walls** |
| Retail Unit Of Measure | **Sold by the individual piece** |

## Packaging

| | |
|---|---|
| Pieces per Carton | **25** |

## Performance + Testing

| | |
|---|---|
| Shade Variation | **V1** |


## Warranties

1 Year Commercial Limited Warranty


## Available Colorways




100 White




300 Sage




400 Glacier



500 Warm Grey



550 Cement Chic



950 Carbon



For reference purposes only if printed or downloaded.

## Additional Information

Per ANSI A326.3, a DCOF of ≥ 0.42 is recommended for tiles in commercial applications. Tiles with a DCOF < 0.42 are not recommended for wet or slippery areas. Contaminants like water, oil, or grease can increase slip risk—use caution when selecting products for such environments. For approved Areas of Application, please reference the chart above. For more information, visit www.tcnatile.com.

Not for use on ramps.

Due to natural variation in ceramic and porcelain tile, final selection should be based on actual product samples.

Ceramic Porcelain Step by Step Installation
Maintenance Guidelines



For reference purposes only if printed or downloaded.