# ShawContract®

## Duality 4.5 X 9 Glossy

*PVC-Free*

| | |
|---|---|
| Style Number | **CT81K** |
| Composition | **Porcelain** |
| Tile Type | **Subway Tile** |
| Body Type | **Glazed Porcelain** |
| Finish | **Glossy** |
| Nominal Dimensions | **4.5" x 9" \| 11.43 cm x 22.86 cm** |
| Actual Dimensions | **4.5" x 9.06" \| 11.43 cm x 23.02 cm** |
| Overall Thickness | **0.334" \| 8.5 mm** |
| Edge Profile | **Pressed** |
| Country Of Origin | **Spain** |
| Installation Area | **Walls** |
| Retail Unit Of Measure | **Sold by the box quantity** |

## Packaging

| | |
|---|---|
| Pieces per Carton | **24** |
| Area per Carton | **6.89 ft²** |
| Weight per Carton | **23.7 lbs** |
| Area per Pallet | **702.78 ft²** |
| Boxes per Pallet | **102 boxes** |

## Recommended Installation Method

Grout Joint Requirement: Minimum of 1/8"

Recommended to grout over pre-scored line.

## Performance + Testing

| | | |
|---|---|---|
| Shade Variation | **V3** | |
| Breaking Strength (ASTM C648) | ≥ **125 lbf** | |
| Water Absorption (ASTM C373) % | ≤ **0.50% (Impervious (Porcelain))** | |
| Frost Resistance (ASTM C1026) | **Resistant** | |
| Chemical Resistance (ASTM C650) | **Class A** | |
| Stain Resistance (ISO 10545-14) | **Class 5** | |
| Wear Rating | ***0 (Walls Only)** | *Not suitable for floors. Use only on walls or vertical surfaces. |

## Areas of Application

| | | | |
|---|---|---|---|
| Interior Walls/Backsplash | ✔ | Interior Wet Plus | |
| Interior Dry Floors | | Exterior Wet Floors | |
| Interior Wet Floors | | Exterior Walls | ✔ |
| Shower Floors | | Oils / Grease | |

## Warranties

1 Year Commercial Limited Warranty



For reference purposes only if printed or downloaded.

# ShawContract®

# Duality 4.5 X 9 Glossy

## Available Colorways



100 Classic


106 Reset


375 Harmony


423 Heritage


506 Antique


675 Renew

## Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

## Additional Information

Per ANSI A326.3, a DCOF of ≥ 0.42 is recommended for tiles in commercial applications. Tiles with a DCOF < 0.42 are not recommended for wet or slippery areas. Contaminants like water, oil, or grease can increase slip risk—use caution when selecting products for such environments. For approved Areas of Application, please reference the chart above. For more information, visit www.tcnatile.com.

Not for use on ramps.

Due to natural variation in ceramic and porcelain tile, final selection should be based on actual product samples.

Ceramic Porcelain Step by Step Installation
Maintenance Guidelines



For reference purposes only if printed or downloaded.